

2.0.4

Cloudera Flow Management Deployment

Date published: 2020-07-17

Date modified: CDP Private Cloud Base

The Cloudera logo is displayed in a bold, orange, sans-serif font. The word "CLOUDERA" is written in all caps, with a stylized 'E' that has three horizontal bars.

<https://docs.cloudera.com/>

Legal Notice

© Cloudera Inc. 2024. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents


CFM deployment workflow.....	4
Understand your deployment scenario.....	5
Prepare your CDP Private Cloud Base cluster.....	5
Install the JDK.....	5
Install and configure a database for NiFi Registry.....	6
Install MySQL.....	6
Configuring NiFi Registry Metadata Stores in MySQL.....	7
Install PostgreSQL.....	8
Configuring NiFi Registry Metadata Stores in PostgreSQL.....	8
Install Cloudera Manager and a CDP Private Cloud Base cluster.....	9
Install the CFM parcel from the repository.....	10
Download the CFM Custom Service Descriptor files.....	11
Install NiFi and NiFi Registry on your Base cluster.....	12
Understand your Base cluster layout.....	12
Add the NiFi service.....	12
Add the NiFi Registry service.....	14
Connect NiFi to NiFi Registry.....	15
Add users or groups to Ranger policies.....	15
Deselect unwanted NiFi Registry dependencies.....	18
Install NiFi and NiFi Registry on a Compute cluster.....	19
Understand your Compute cluster layout.....	19
Create a Shared Data Context.....	20
Add the NiFi and NiFi Registry groups to Ranger in the Base cluster.....	21
Create a Compute cluster.....	22
Add the NiFi and NiFi Registry services to a Compute cluster.....	23
Connect NiFi to NiFi Registry.....	25
Add users or groups to Ranger policies.....	26
Deselect unwanted NiFi Registry dependencies.....	28
Install NiFi on a Compute cluster and NiFi Registry on a Base cluster.....	29
Understand your mixed cluster layout.....	29
Install NiFi Registry on your Base cluster.....	30
Create a Shared Data Context.....	31
Add NiFi and NiFi Registry groups to Ranger.....	32
Create Compute cluster.....	33
Add NiFi to the Compute cluster.....	34
Create NiFi node users.....	35
Connect NiFi to NiFi Registry.....	36
Add users or groups to Ranger.....	37
Deselect unwanted NiFi Registry dependencies.....	39

CFM deployment workflow

Before you get started with your Cloudera Flow Management deployment, it is helpful to understand the steps involved.

**Tip:**

The workflow diagram is clickable. Click each step or choice to go directly to the relevant documentation.



rect 241, 166, 374, 262 [Link to documentation for preparing your CDP Private Cloud Base](#)

rect 175, 307, 443, 455 >[Link to documentation describing your deployment scenario](#)

rect 22, 521, 190, 619 [Link to documentation for installing NiFi and NiFi Registry on a Base cluster](#)

rect 223, 522, 391, 615 [Link to documentation for installing NiFi and NiFi Registry on a Compute cluster](#)

rect 424, 526, 594, 612 [Link to documentation for installing NiFi on a Compute cluster and NiFi Registry on a Base cluster](#)

Understand your deployment scenario

There are three main installation scenarios for installing CFM on a CDP Private Cloud Base cluster, and it is helpful to understand the difference between them before you get started with your CFM deployment.

Install NiFi and NiFi Registry on a Base cluster

A Base cluster is a large cluster that contains SDX services like Ranger and Atlas, as well as compute and storage services like NiFi, Impala, and Hive.

A Base cluster is sometimes called a Regular cluster in Cloudera Manager. It is also known as an SDX cluster, a Shared cluster, or a Data Lake cluster.



Tip:

Cloudera recommends that you always install NiFi Registry on your Base cluster.

Installing NiFi on your Base cluster is a simplified deployment during which you create only one cluster. You can do this if you are deploying one cluster in trial deployments or in simple production scenarios.

Install NiFi and NiFi Registry on a Compute cluster

A Compute cluster consists exclusively of compute nodes. A Compute cluster is then connected to a Base cluster with SDX services like Ranger and Atlas, using a Shared Data Context.

Installing NiFi on a Compute cluster is recommended when you want to deploy multiple NiFi clusters for larger scale production deployments, when you want to isolate your dataflows, when you want to have different authorization models per dataflow, and other similar deployment scenarios.

Install NiFi on a Compute cluster and NiFi Registry on a Base cluster

You can also install NiFi on one or more Compute clusters and NiFi Registry on your Base cluster.



Tip:

Cloudera recommends that you use this layout for production deployments.

Install NiFi on a Compute cluster and NiFi Registry on your Base cluster when you want to share dataflows across multiple NiFi Compute clusters in your CDP environment.

Review *CFM deployment workflow* to understand the steps required for each scenario.

Related Information

[CFM deployment workflow](#)

Prepare your CDP Private Cloud Base cluster

You should complete the following steps to prepare your CDP Private Cloud Base cluster.

Install the JDK

You should install JDK on each machine on which you will install NiFi, if your version of Cloudera Manager is not already configured with JDK.

About this task

The following Java versions are supported:

- Java 1.8
- Java 1.11



Note: Java 11.0.8 or later is supported.

Procedure

1. Download JDK from the appropriate website.
2. Run the installation command appropriate for your operating system:

For RHEL/CentOS:

```
yum install java-1.8.0-openjdk-devel
```

What to do next

Once you have installed the JDK, ensure that you have the required database installed and set up for NiFi Registry.

Related Information

[Open JDK Download](#)

[Oracle JDK Download](#)

Install and configure a database for NiFi Registry

If you are installing NiFi Registry, you can install and configure an external MySQL or PostgreSQL database. By default, NiFi Registry is pre-configured to use an embedded H2 database.

H2 is an embedded database that is preconfigured in the default `nifi.registry.properties` file. The contents of the H2 database are stored in a file on your local file system. The H2 database location is specified as part of the JDBC URL property:

- NiFi Registry JDBC Url (`nifi.registry.db.url`) – `jdbc:h2:./database/nifi-registry-primary`

If you plan to use the H2 embedded database, you can skip the steps for installing and configuring an external database. Alternately, you may install a MySQL or PostgreSQL external database. To do this, review the following steps for either MySQL or PostgreSQL.

For a list of supported MySQL or PostgreSQL databases, see [Supported NiFi Registry databases](#).

Install MySQL

Learn how to install a MySQL external database for NiFi Registry.

About this task

If you have already installed a PostgreSQL database, you may skip these steps. Both databases are not required.

For a list of supported MySQL databases, see [Supported NiFi Registry databases](#).

Procedure

1. Log in to the node on which you want to install NiFi Registry.
2. Install MySQL and the MySQL community server, and start the MySQL service:

```
yum localinstall \  
https://dev.mysql.com/get/mysql57-community-release-el7-8.noarch.rpm
```

```
yum install mysql-community-server
systemctl start mysqld.service
```

3. Obtain the randomly generated MySQL root password:

```
grep 'A temporary password is generated for root@localhost' \
/var/log/mysqld.log |tail -1
```

4. Reset the MySQL root password. Enter the following command. You are prompted for the password you obtained in the previous step. MySQL then asks you to change the password:

```
/usr/bin/mysql_secure_installation
```

What to do next

Once you have completed the MySQL installation, configure it for use with NiFi Registry.

Configuring NiFi Registry Metadata Stores in MySQL

Learn how to configure a MySQL database for use with NiFi Registry.

About this task

MySQL provides the option to use an externally located database that supports high availability.

Procedure

1. Download the MySQL JDBC driver and place it somewhere accessible to NiFi Registry:

```
/path/to/drivers/mysql-connector-java-8.0.16.jar
```

2. Create a database inside MySQL (enter mysql shell using `mysql -u root -p`):

```
CREATE DATABASE nifi_registry;
```

3. Create a database user and grant privileges (for remote users, use `nifireg'@'<IP-ADDRESS>` or `nifireg'@'%'` for any remote host):

```
GRANT ALL PRIVILEGES ON nifi_registry.* TO 'nifireg'@'localhost' IDENTIFIED BY 'changeme';
```

4. After NiFi Registry service is installed, configure the database properties in Cloudera Manager:

- NiFi Registry JDBC Url (`nifi.registry.db.url`) – `jdbc:mysql://<MYSQL-HOSTNAME>/nifi_registry`
- NiFi Registry JDBC Driver (`nifi.registry.db.driver.class`) – `com.mysql.cj.jdbc.Driver`
- NiFi Registry H2 directory storage location (`nifi.registry.db.driver.directory`) – `/path/to/drivers`



Note:

The NiFi Registry H2 directory storage location field specifies the NiFi Registry database driver directory. The H2 database is used by default. Update this field when you are configuring it for an external database.

- NiFi Registry Database Username (`nifi.registry.db.username`) – `nifireg`
- NiFi Registry Database Password (`nifi.registry.db.password`) – `changeme`

What to do next

When you have completed the NiFi Registry database configuration, move on to installing Cloudera Manager and your CDP Private Cloud Base Cluster.

Install PostgreSQL

Learn how to install a PostgreSQL external database for use with NiFi Registry.

About this task

If you have already installed a MySQL database, you may skip these steps. Both databases are not required.

For a list of supported PostgreSQL databases, see [Supported NiFi Registry databases](#).

Procedure

1. Install Red Hat Package Manager (RPM) according to the requirements of your operating system:

```
yum install https://yum.postgresql.org/9.6/redhat/rhel-7-x86_64/pgdg-redhat96-9.6-3.noarch.rpm
```

2. Install Postgres version 9.x or 10.x:

```
yum install postgresql96-server postgresql96-contrib postgresql96
```

3. Initialize the database.

For CentOS 7, use the following syntax:

```
/usr/pgsql-9.6/bin/postgresql96-setup initdb
```

4. Start Postgres.

For example, if you are using CentOS 7, use the following syntax:

```
systemctl enable postgresql-9.6.service
systemctl start postgresql-9.6.service
```

5. Verify that you can log in:

```
sudo su postgres
psql
```

What to do next

Once you have installed PostgreSQL, configure the database for use with NiFi Registry.

Configuring NiFi Registry Metadata Stores in PostgreSQL

Learn how to configure a PostgreSQL database for use with NiFi Registry.

About this task

Postgres provides the option to use an externally located database that supports high availability.

Procedure

1. Download the Postgres JDBC driver and place it somewhere accessible to NiFi Registry:

```
/path/to/drivers/postgresql-42.2.2.jar
```

2. Create a database inside Postgres:

```
createdb nifireg
```

3. Create a database user and grant privileges:

```
psql nifireg
CREATE USER nifireg WITH PASSWORD 'changeme';
GRANT ALL PRIVILEGES ON DATABASE nifireg to nifireg;
\q
```

4. After NiFi Registry service is installed, configure the database properties in Cloudera Manager:

- NiFi Registry JDBC Url (nifi.registry.db.url) – jdbc:postgresql://<POSTGRES-HOSTNAME>/nifireg
- NiFi Registry JDBC Driver (nifi.registry.db.driver.class) – org.postgresql.Driver
- NiFi Registry H2 directory storage location (nifi.registry.db.driver.directory) – /path/to/drivers



Note:

The NiFi Registry H2 directory storage location field specifies the NiFi Registry database driver directory. The H2 database is used by default. Update this field when you are configuring it for an external database.

- NiFi Registry Database Username (nifi.registry.db.username) – nifireg
- NiFi Registry Database Password (nifi.registry.db.password) – changeme

What to do next

When you have completed the NiFi Registry database configuration, move on to installing Cloudera Manager and your CDP Private Cloud Base Cluster.

Install Cloudera Manager and a CDP Private Cloud Base cluster

Learn about the basic requirements for installing Cloudera Manager and CDP Private Cloud Base.

About this task

You should follow the instructions in the *CDP Private Cloud Base Installation Guide* for complete information about installing Cloudera Manager and a CDP base cluster. At minimum, you should ensure that you perform the following steps.

Before you begin

- You have installed a JDK
- If you want to use an external database, you have installed and configured it for NiFi Registry.

Procedure

1. Install CDP Private Cloud Base.

See the *CDP Private Cloud Base Installation Guide* for more information.

2. Enable Auto-TLS and Kerberos.

Cloudera recommends the following security configuration:

- Enable Auto-TLS.
- Enable Kerberos.
- Use Apache Atlas for dataset level lineage graphs.
- Use Apache Ranger to authorize NiFi and NiFi Registry users.

For details on security recommendations and options, see *CFM Security*.



Note:

Wildcard certificates are not supported.

- If NiFi or NiFi Registry is behind Knox, do not use wildcard certificates for Knox.
- Do not generate wildcard certificates for the NiFi nodes. For example, if two nodes, node1.nifi.apache.org and node2.nifi.apache.org, are assigned the same certificate with a CN or SAN entry of *.nifi.apache.org, this certificate will not be supported.

For more information on certificate requirements, see *TLS certificate requirements and recommendations*.

3. Install the following Runtime services, at minimum:

- Atlas
- Ranger
- ZooKeeper

What to do next

When you have completed the CDP Private Cloud Base cluster installation, add the CFM parcel and CSD files.

Related Information

[CDP Private Cloud Base Installation Guide](#)

[CFM Security](#)

[TLS certificate requirements and recommendations](#)

Install the CFM parcel from the repository

Install the CFM parcel to make NiFi and NiFi Registry available for installation. To install the CFM parcel to Cloudera Manager, you must update the Parcel URL, and then download, distribute and activate the CFM parcel.

Before you begin

- You have installed a JDK.
- You have installed and configured a database for use with NiFi Registry.
- You have installed a CDP Private Cloud Base cluster.

Procedure

1. Navigate to the Parcels page.
2. From the navigation bar, select **Hosts** **Parcels** and click **Parcel Repository & Network Settings**.
3. On the **Parcel Repository & Network Settings** page, click **+** to add an additional row in the **Remote Parcel Repository URLs** list.

4. Add the URL of the CFM parcel you want to install.
See *Download Locations* for a complete list of parcels.
For example:

```
https://archive.cloudera.com/p/CFM/2.x/redhat7/yum/tars/parcel/CFM-2.0.4.0-80-el7.parcel
```

5. Click Save & Verify Configuration.
6. Click Close.
The new CFM parcel displays with the set of parcels available for download on the Parcels page.
7. From the Parcels page, download, distribute, and activate the CFM parcel.

What to do next

When you have finished downloading, distributing and activating the CFM parcel, add the CSD files for use by Cloudera Manager Server.

Related Information

[Download locations](#)

Download the CFM Custom Service Descriptor files

A Custom Service Descriptor (CSD) file contains configuration information needed to describe and manage a new service. Download the CSDs for each CFM Service, specify ownership and permissions, and then restart the Cloudera Manager Server.

Procedure

1. Download the CSDs for NiFi and NiFi Registry and put them into `/opt/cloudera/csd`.
You can download the files from the CFM repository. See *Download Locations*.



Important:

Ensure that the CSD version is the same as the CFM version. Different CSD and CFM versions can cause problems when configuring and managing NiFi through Cloudera Manager.

2. Change the CSD owner. In `opt/cloudera/csd`, enter:

```
chown cloudera-scm:cloudera-scm ./*
chmod 644 ./*
```

3. Restart the Cloudera Manager Server.

```
sudo service cloudera-scm-server restart
```

4. Restart the Cloudera Management Service. From the Cloudera Manager Status tab, select Restart from the Cloudera Management Service drop-down.

What to do next

When you have finished adding the CSD files, you have completed your CDP Private Cloud Base installation. You can now proceed with installing, securing, and configuring CFM.

Review *CFM deployment workflow* and *Understand your deployment scenario* for help deciding whether to install NiFi on a Base cluster or on a Compute cluster. Then follow the tasks outlined in *Install NiFi on your Base cluster* or *Install NiFi on a Compute cluster*.

Related Information

[Download locations](#)

[CFM deployment workflow](#)

[Understand your deployment scenario](#)

[Install NiFi and NiFi Registry on your Base cluster](#)

[Install NiFi and NiFi Registry on a Compute cluster](#)

Install NiFi and NiFi Registry on your Base cluster

Provides the steps to add and configure NiFi and NiFi Registry to a CDP Private Cloud Base Base cluster.

Understand your Base cluster layout

Provides an explanation of a Base cluster installation and information about the Base cluster layout.

A Base cluster is a large cluster that contains SDX services like Ranger and Atlas, as well as compute and storage services like NiFi, Impala, and Hive.


A Base cluster is sometimes called a Regular cluster in Cloudera Manager. It is also known as an SDX cluster, a Shared cluster, or a Data Lake cluster.

**Tip:**

Cloudera recommends that you always install NiFi Registry on your Base cluster.

Installing NiFi on your Base cluster is a simplified deployment during which you create only one cluster. You can do this if you are deploying one cluster in trial deployments or in simple production scenarios.

When you install both NiFi and NiFi Registry on your Base cluster, your cluster layout will look similar to the following:



Add the NiFi service


Provides the steps for adding and configuring the NiFi service to a CDP Private Cloud Base cluster.

Before you begin

You have installed a CDP Private Cloud Base cluster.

Procedure

1. From Home > Status tab, select the drop-down to the right of your cluster, and select Add Service. Install one service at a time.



2. Specify that you want to add the NiFi service and click Continue to display the Add Service wizard.
3. Select NiFi dependencies and click Continue.

- ZooKeeper is a required dependency.
- Select Knox if you want a single entry point to securely access the services.
- Cloudera recommends that you also select Ranger and Atlas dependencies.

4. Assign Roles to your NiFi service.

Select the hosts onto which you want to install your new NiFi roles. Click Continue.



Note: If you selected Knox as a dependency, then install Knox and NiFi on different nodes because Knox, by default, has a port conflict on 8443.

5. Review changes to your configuration. Click Continue. This will start the service installation.

Provide a value for your Initial Admin Identity. You may choose to further customize your NiFi configuration here.



Note:

You must add any group name or identity set by these three parameters to Ranger, in order for your installation install to succeed.

- Initial Admin Identity (nifi.initial.admin.identity)
- NiFi proxy group (nifi.proxy.group)
- Initial Admin Groups (nifi.initial.admin.groups)

6. Click Continue and Finish to complete the installation.

7. Open a browser and enter the URL to the NiFi UI.

The URL format for the NiFi UI is based on whether or not you selected Knox as a dependency during the installation:

- If you did not select Knox, the URL format is:

```
https://[***HOSTNAME***]:8443/nifi
```

- If you selected Knox, use the Knox URL as a single entry point to securely access all NiFi nodes and switch nodes if one fails. The format is:

```
https://[***KNOX-GATEWAY-HOSTNAME***]:[***KNOX-GATEWAY-PORT***]/gateway/cdp-proxy/nifi-app/nifi/
```

Results

Verify the new service is added properly by checking the health status for the new service. If the Health Status is Good, then the service added properly.

What to do next

When you have finished adding the NiFi service, proceed with adding the NiFi Registry service.

Add the NiFi Registry service


Provides the steps for adding and configuring the NiFi Registry service.

Before you begin

You have added the NiFi Service to a cluster.

Procedure

1. From Home > Status tab, select the drop-down to the right of your cluster, and select Add a Service. Install one service at a time.



2. Specify that you want to add the NiFi Registry service and click Continue to display the Add Service wizard.
3. Select NiFi Registry dependencies and click Continue.

Cloudera recommends that you select NiFi and Ranger dependencies.



Note:

NiFi Registry does not require any dependencies. However, if you select No Optional Dependencies, some services are still selected as dependencies. You can deselect unwanted dependencies once you have finished the installation.

4. Assign Roles to your NiFi Registry service.
Select the host onto which you want to install your new NiFi Registry role. Click Continue.
5. Review changes to your configuration. Click Continue to start the service installation.

Provide a value for your Initial Admin Identity. You may choose to further customize your NiFi configuration here.



Note:

You must add any group name or identity set by these three parameters to Ranger, in order for your installation install to succeed.

- Initial Admin Identity (nifi.registry.initial.admin.identity)
- NiFi Registry proxy group (nifi.registry.proxy.group)
- Initial Admin Groups (nifi.registry.initial.admin.groups)

6. Click Continue and Finish to complete the installation.
7. Open a browser and enter the URL to the NiFi Registry UI.

The URL format for the NiFi Registry UI is based on whether or not you selected Knox as a dependency during the installation:

- If you did not select Knox, the URL format is:

```
https://[***HOSTNAME***]:18443/nifi-registry
```

- If you selected Knox, use the Knox URL as a single entry point to securely access all NiFi Registry nodes and switch nodes if one fails. The format is:

```
https://[***KNOX-GATEWAY-HOSTNAME***]:[***KNOX-GATEWAY-PORT***]/gateway/cdp-proxy/nifi-registry-app/nifi-registry/
```

Results

Verify the new service is added properly by checking the health status for the new service. If the Health Status is Good, then the service added properly.

What to do next

When you have finished adding the NiFi Registry service, proceed by connecting NiFi to NiFi Registry.

Connect NiFi to NiFi Registry

Provides the steps to connect NiFi to NiFi Registry.

Before you begin

- You have added and configured NiFi and NiFi Registry.
- You have started both NiFi and NiFi Registry.

Procedure

1. From the NiFi UI, select Controller Settings from the Global Menu.
2. Select the Registry Clients tab.
3. Click the Add icon (+) to launch the Add Registry Client dialog.
4. Add the name and URL location of the NiFi Registry service you just created.

Results

NiFi Settings

GENERAL	REPORTING TASK CONTROLLER SERVICES	REPORTING TASKS	REGISTRY CLIENT
---------	------------------------------------	-----------------	-----------------

Name ▲	Location
NiFi Registry	https://cfm-node-3.cloudera.com:18433

What to do next

Once you have connected NiFi and NiFi Registry, complete additional post-installation configuration steps to complete your installation.

Add users or groups to Ranger policies

Provides steps to add users or groups to Ranger Policies.

About this task

Determine what the user can command, control, and observe in a NiFi dataflow or in NiFi Registry and accordingly add the user or a group of users to the appropriate pre-defined Ranger access policies.

Each pre-defined Ranger access policy confers specific rights to NiFi or NiFi Registry resources.

For more information, see:

- *Pre-defined Ranger access policies for NiFi resources*
- *Pre-defined Ranger access policies for NiFi Registry resources*


Before you begin

- You have installed Ranger on your Base CDP Private Cloud Base cluster.
- You have added and connected the NiFi and NiFi Registry services.

Procedure

1. From the Base cluster, select Ranger from the list of services. Click Ranger Admin Web UI and log into Ranger.

The **Ranger Service Manager** page displays.



Each cluster in the environment is listed under its respective service. For example, the NiFi clusters in the environment are listed under NiFi.

- Select a cluster from either the NiFi or NiFi Registry section.
The **List of Policies** page appears.

Ranger Access Manager Audit Security Zone Settings admin

Service Manager Cluster 1_nifi Policies

List of Policies : Cluster 1_nifi

Search for your policy.. + ? [Add New Policy](#)

Policy ID	Policy Name	Policy Labels	Status	Audit Logging	Roles	Groups	Users	Action
41	Restricted Components	--	Enabled	Enabled	--	nifi	admin	  
42	Provenance	--	Enabled	Enabled	--	nifi	admin	  
43	Flow	--	Enabled	Enabled	--	nifi	admin	  
44	Tenants	--	Enabled	Enabled	--	nifi	admin	  
45	Controller	--	Enabled	Enabled	--	nifi	admin	  
46	Policies	--	Enabled	Enabled	--	nifi	admin	  
47	Proxies	--	Enabled	Enabled	--	nifi	--	  
48	Root Process Group	--	Enabled	Enabled	--	nifi	admin	  
49	Root Process Group Provenance Data	--	Enabled	Enabled	--	nifi	admin	  
50	Root Process Group Data	--	Enabled	Enabled	--	nifi	admin	  

- Click the ID for a policy.
The **Edit Policy** page appears.

The screenshot shows the 'Edit Policy' page in the Ranger interface. The breadcrumb trail is 'Service Manager > Cluster 1_nifi Policies > Edit Policy'. The page title is 'Edit Policy'.

Policy Details :

- Policy Type: **Access**
- Policy ID: **43**
- Policy Name: **Flow** (with a dropdown arrow)
- Policy Label: **Policy Label**
- NiFi Resource Identifier: **/flow**
- Description: (empty text area)
- Audit Logging: **YES**
- Buttons: **enabled** (selected), **normal** (disabled), **Add Validity Period**

Allow Conditions :

Select Role	Select Group	Select User	Permissions	Delegate Admin	
Select Roles	nifi	admin	Read (with edit icon)	☐	X
+					

Deny All Other Accesses : **False**

Buttons: **Save**, **Cancel**, **Delete**

- In the Allow Conditions section, add the user or the user group to the Select User field.
- Click Save.

Results

The user now has the NiFi and NiFi Registry rights according to the policies you added the user or user group to. These rights are inherited down the hierarchy unless there is a more specific policy on a component.

What to do next

When you have completed the steps for adding users and groups to Ranger policies, review the steps to deselect unwanted NiFi Registry dependencies and determine whether this task applies to you.

Related Information

[Pre-defined Ranger access policies for Apache NiFi](#)

[Pre-defined Ranger access policies for Apache NiFi Registry](#)

Deselect unwanted NiFi Registry dependencies

Provides steps to remove unwanted NiFi Registry dependencies.

About this task


This is an optional task. During your cluster installation, some dependencies may have been added to NiFi Registry. If you do not want these dependencies, follow these steps to remove them.

Before you begin

- You have installed a CDP Private Cloud Base cluster.
- You have added the NiFi Registry service.

Procedure

1. From Cloudera Manager, click the Clusters tab in the left-hand navigation
2. Click NiFi Registry in the list of services to display the NiFi Registry service page.
3. Select the Configuration tab.
4. Deselect any unwanted dependencies.



5. Click Save Changes. Restart the NiFi Registry service.

What to do next

You have completed your CDP Private Cloud Base cluster and CFM installation.

Install NiFi and NiFi Registry on a Compute cluster

Provides the steps to add and configure NiFi and NiFi Registry to a CDP Private Cloud Base Compute cluster.


Understand your Compute cluster layout

Provides an explanation of a Compute cluster installation and information about the cluster layout.

A Compute cluster consists exclusively of compute nodes. A Compute cluster is then connected to a Base cluster with SDX services like Ranger and Atlas, using a Shared Data Context.

Installing NiFi on a Compute cluster is recommended when you want to deploy multiple NiFi clusters for larger scale production deployments, when you want to isolate your dataflows, when you want to have different authorization models per dataflow, and other similar deployment scenarios.

When you install both NiFi and NiFi Registry on a Compute cluster, your cluster layout will look similar to the following:



Create a Shared Data Context

Provides the steps to create a Shared Data Context.

Before you begin

- You have reviewed *Understand your deployment scenario* and have decided to install NiFi on a Compute cluster.
- You have prepared your CDP Private Cloud Base Base cluster.
- Your Base cluster has data, metadata, and security services to share.

Procedure

1. From Cloudera Manager Home, click on your Base cluster name to go the Detail page.
2. In the Data Contexts section, click Create.
3. In the Create Data Context dialog, provide a Data Context Name, specify your Base cluster, and click Create.

Example

Create Data Context



A Data Context, part of [Cloudera SDX \(Shared Data Experience\)](#), allows you to share data, metadata, and security services from a Base Cluster. You can then use it to create **separate Compute Clusters**.

Data Context Name

Base Cluster

Only version 5.15 or higher is supported.

Data Services

☒ HDFS

Metadata Services

☒ Hive

Security Services

☒ Atlas

☒ Ranger

Cancel

Create

What to do next

When you have finished creating a Shared Data Context, proceed to creating a Compute cluster.

Add the NiFi and NiFi Registry groups to Ranger in the Base cluster

Provides steps to add the NiFi and NiFi Registry groups in Ranger.

About this task



Note:

If the CFM parcel has been activated on the Base cluster, the nifi and nifi registry groups in Ranger are automatically created and you may skip this task.

If your Compute cluster uses a Shared Data Context that shares the Ranger service, you must create the nifi and nifi registry groups in Ranger on the Base cluster. You must create these groups before you install the NiFi and NiFi Registry service on the Compute cluster, in order for the required NiFi and NiFi Registry Ranger access policies to be created.

Before you begin

- You have created a Shared Data Context.

Procedure

1. Go to Ranger.
2. Select Settings > Users/Groups/Roles
The **Users/Groups/Roles** page appears.
3. Select the Groups tab, then click Add New Group.
The **Group Detail** page appears.
4. For Group Name, enter nifi. Click Save.
5. Click Add New Group.
6. For Group Name, enter nifiregistry. Click Save.

What to do next

When you have finished creating the Ranger groups, proceed to creating a Compute cluster.

Create a Compute cluster

Provides the steps to create a CDP Private Cloud Base Compute cluster.

About this task

You should follow the instructions in the *CDP Installation Guide* for complete information about installing Cloudera Manager and a CDP base cluster. At minimum, you should ensure that you perform the following steps.

Before you begin

- You have prepared your CDP Private Cloud Base Base cluster.
- You have created a Shared Data Context in your Base cluster.

Procedure

1. Launch the Add Cluster – Installation wizard.
From your Base cluster detail page, select Add Compute Cluster from the Actions drop-down.

- From the Cluster Basics step, add a cluster name, and select your Shared Data Context from the Data Context drop-down. Click Continue.

Add Cluster - Installation

Cluster Basics

Cluster Name: CFM Compute Cluster

Compute Cluster **Base Cluster**

A Compute Cluster consists of only compute nodes. To connect to existing storage, metadata or security services, you must first choose or create a **Data Context** on a Base Cluster. Learn more at [Cloudera SDX Technologies](#).

Data Context: shared-data-context

Data Services
HDFS-1

Metadata Services
None

Security Services
RANGER-1
ATLAS-1

Back Continue

- From the Specify Hosts step, select the hosts you want to belong to your Compute cluster. Click Continue.
- From the Select Repository step, select the CFM parcel. If the CFM parcel has not been added yet, select Parcel Repositories & Network Settings and add the CFM Parcel URL
See *Install the CFM parcel from the repository* for more information.
The CDH parcel is added by default. Click Continue to download, distribute, and activate the CFM and CDH parcels.
- From the Inspect Cluster step, run the Inspect Network Performance and Inspect Hosts inspections. Click Continue to select services to install.

What to do next

When you have finished creating your Compute cluster, proceed by adding the NiFi and NiFi Registry services.

Related Information

[CDP Data Center Installation Guide](#)

[CFM Security](#)

Add the NiFi and NiFi Registry services to a Compute cluster

Provides the steps for adding and configuring the NiFi and NiFi Registry services to a Compute cluster.

Before you begin

- You have created a Shared Data Context and a Compute cluster.
- You have added the nifi and nifi registry groups to Ranger in the Base cluster.

- You have created a Compute cluster with CDH and CFM parcels installed.

Procedure

1. After your Compute cluster is created, the Add Cluster - Configuration wizard displays.
2. From the Select Services step, select Custom Services. Select NiFi and NiFi Registry. Click Continue.
3. From the Assign Roles step, select the hosts onto which you want to install your new NiFi roles and the host onto which you want to install your NiFi Registry role.

ZooKeeper is a required dependency of NiFi. Select the hosts onto which you want to install ZooKeeper. Click Continue.

4. From the Review Changes step, review changes to your configuration. For both NiFi and NiFi Registry, provide a value for your Initial Admin Identity. You may choose to further customize your NiFi and NiFi Registry configurations here.



Note:

You must add any group name or identity set by these parameters to Ranger, in order for your installation install to succeed.

For NiFi:

- Initial Admin Identity (nifi.initial.admin.identity)
- NiFi proxy group (nifi.proxy.group)
- Initial Admin Groups (nifi.initial.admin.groups)

For NiFi Registry:

- Initial Admin Identity (nifi.registry.initial.admin.identity)
- NiFi Registry proxy group (nifi.registry.proxy.group)
- Initial Admin Groups (nifi.registry.initial.admin.groups)

Click Continue.

5. From the Configure Kerberos step, install Kerberos client libraries on all Compute cluster hosts as needed. Click Continue to initiate the Kerberos enablement.
6. When you have completed these steps for both NiFi and NiFi Registry, click Continue. This starts the NiFi and NiFi Registry services installation.
7. Click Continue and Finish to complete the installation.

8. Open a browser and enter the URL to the NiFi and NiFi Registry UI.

The URL format for the UIs is based on whether or not you selected Knox as a dependency during the installation:

- If you did not select Knox, the URL format is:

- NiFi:

```
https://[***HOSTNAME***]:8443/nifi
```

- NiFi Registry:

```
https://[***HOSTNAME***]:18443/nifi-registry
```

- If you selected Knox, use the Knox URL as a single entry point to securely access all NiFi and NiFi Registry nodes and switch nodes if one fails. The format is:

- NiFi:

```
https://[***KNOX-GATEWAY-HOSTNAME***]:[***KNOX-GATEWAY-PORT***]/gateway/cdp-proxy/nifi-app/nifi/
```

- NiFi Registry:

```
https://[***KNOX-GATEWAY-HOSTNAME***]:[***KNOX-GATEWAY-PORT***]/gateway/cdp-proxy/nifi-registry-app/nifi-registry/
```

Results

Verify the new services are added properly by checking the health status for the new services. If the Health Status is Good, then the services added properly.

What to do next

When you have finished adding the NiFi and NiFi Registry services, proceed by connecting NiFi to NiFi Registry.

Connect NiFi to NiFi Registry

Learn about the steps to configure NiFi to identify the NiFi Registry so that you can support versioned flows in Cloudera Flow Management.

Before you begin

- You have added and configured NiFi and NiFi Registry.
- You have started both NiFi and NiFi Registry.

Procedure

1. From the NiFi UI, select Controller Settings from the Global Menu.
2. Select the Registry Clients tab.
3. Click the Add icon (+) to launch the Add Registry Client dialog.
4. Add the name and URL location of the NiFi Registry service you just created.

Results

NiFi Settings

GENERAL	REPORTING TASK CONTROLLER SERVICES	REPORTING TASKS	REGISTRY CLIENT
---------	------------------------------------	-----------------	-----------------

Name ▲	Location
NiFi Registry	https://cfm-node-3.cloudera.com:18433

What to do next

Once you have connected NiFi and NiFi Registry, complete additional post-installation configuration steps to complete your installation.

Add users or groups to Ranger policies

Provides steps to add users or groups to Ranger Policies.

About this task

Determine what the user can command, control, and observe in a NiFi dataflow or in NiFi Registry and accordingly add the user or a group of users to the appropriate pre-defined Ranger access policies.

Each pre-defined Ranger access policy confers specific rights to NiFi or NiFi Registry resources.

For more information, see:


- *Pre-defined Ranger access policies for NiFi resources*
- *Pre-defined Ranger access policies for NiFi Registry resources*

Before you begin

- You have installed Ranger on your Base CDP Private Cloud Base cluster.
- You have added and connected the NiFi and NiFi Registry services.


Procedure

- From the Base cluster, select Ranger from the list of services. Click Ranger Admin Web UI and log into Ranger. The **Ranger Service Manager** page displays.



Each cluster in the environment is listed under its respective service. For example, the NiFi clusters in the environment are listed under NiFi.

- Select a cluster from either the NiFi or NiFi Registry section. The **List of Policies** page appears.



- Click the ID for a policy.
The **Edit Policy** page appears.

Ranger Access Manager Audit Security Zone Settings admin

Service Manager > Cluster 1_nifi Policies > Edit Policy

Edit Policy

Policy Details :

Policy Type: **Access** Add Validity Period

Policy ID: **43**

Policy Name *: Flow enabled normal

Policy Label: Policy Label

NiFi Resource Identifier *: /flow

Description:

Audit Logging: **YES**

Allow Conditions : hide

Select Role	Select Group	Select User	Permissions	Delegate Admin	
Select Roles	/nifi	/admin	Read	☐	x

+

Deny All Other Accesses : **False**

Save **Cancel** **Delete**

- In the Allow Conditions section, add the user or the user group to the Select User field.
- Click Save.

Results

The user now has the NiFi and NiFi Registry rights according to the policies you added the user or user group to. These rights are inherited down the hierarchy unless there is a more specific policy on a component.

What to do next

When you have completed the steps for adding users and groups to Ranger policies, review the steps to deselect unwanted NiFi Registry dependencies and determine whether this task applies to you.

Deselect unwanted NiFi Registry dependencies

Provides steps to remove unwanted NiFi Registry dependencies.

About this task


This is an optional task. During your cluster installation, some dependencies may have been added to NiFi Registry. If you do not want these dependencies, follow these steps to remove them.

Before you begin

- You have installed a CDP Private Cloud Base cluster.
- You have added the NiFi Registry service.

Procedure

1. From Cloudera Manager, click the Clusters tab in the left-hand navigation
2. Click NiFi Registry in the list of services to display the NiFi Registry service page.
3. Select the Configuration tab.
4. Deselect any unwanted dependencies.



5. Click Save Changes. Restart the NiFi Registry service.

What to do next

You have completed your CDP Private Cloud Base Compute cluster and CFM installation.

Install NiFi on a Compute cluster and NiFi Registry on a Base cluster

Provides the steps to add and configure NiFi on a Compute cluster and NiFi Registry on a Base cluster.

Understand your mixed cluster layout

Provides an explanation of a mixed cluster installation and information about the cluster layout.

You can also install NiFi on one or more Compute clusters and NiFi Registry on your Base cluster.




Tip:

Cloudera recommends that you use this layout for production deployments.

Install NiFi on a Compute cluster and NiFi Registry on your Base cluster when you want to share dataflows across multiple NiFi Compute clusters in your CDP environment.

When you install both NiFi on one or more Compute clusters, and NiFi Registry on your Base cluster, your cluster layout will look similar to the following:



Install NiFi Registry on your Base cluster


Provides the steps for adding and configuring the NiFi Registry service.

Before you begin

You have prepared your CDP Base cluster.

Procedure

1. From Home > Status tab, select the drop-down to the right of your cluster, and select Add a Service. Install one service at a time.



2. Specify that you want to add the NiFi Registry service and click Continue to display the Add Service wizard.

3. Select NiFi Registry dependencies and click Continue.

Cloudera recommends that you select NiFi and Ranger dependencies.



Note:

NiFi Registry does not require any dependencies. However, if you select No Optional Dependencies, some services are still selected as dependencies. You can deselect unwanted dependencies once you have finished the installation.

4. Assign Roles to your NiFi Registry service.

Select the host onto which you want to install your new NiFi Registry role. Click Continue.

5. Review changes to your configuration. Click Continue to start the service installation.

Provide a value for your Initial Admin Identity. You may choose to further customize your NiFi configuration here.



Note:

You must add any group name or identity set by these three parameters to Ranger, in order for your installation install to succeed.

- Initial Admin Identity (nifi.registry.initial.admin.identity)
- NiFi Registry proxy group (nifi.registry.proxy.group)
- Initial Admin Groups (nifi.registry.initial.admin.groups)

6. Click Continue and Finish to complete the installation.

Results

Verify the new service is added properly by checking the health status for the new service. If the Health Status is Good, then the service added properly.

What to do next

When you have finished adding the NiFi Registry service, proceed by creating a Shared Data Context for your Compute cluster.

Create a Shared Data Context

Provides the steps to create a Shared Data Context.

Before you begin

- You have reviewed *Understand your deployment scenario* and have decided to install NiFi on a Compute cluster.
- You have prepared your CDP Private Cloud Base Base cluster.
- Your Base cluster has data, metadata, and security services to share.

Procedure

1. From Cloudera Manager Home, click on your Base cluster name to go the Detail page.
2. In the Data Contexts section, click Create.
3. In the Create Data Context dialog, provide a Data Context Name, specify your Base cluster, and click Create.

Example

Create Data Context



A Data Context, part of [Cloudera SDX \(Shared Data Experience\)](#), allows you to share data, metadata, and security services from a Base Cluster. You can then use it to create **separate Compute Clusters**.

Data Context Name

Base Cluster

Datalake (7.1.1) ▼

Only version 5.15 or higher is supported.

Data Services

☒ HDFS

Metadata Services

☒ Hive

Security Services

☒ Atlas

☒ Ranger

Cancel

Create

What to do next

When you have finished creating a Shared Data Context, proceed to adding NiFi and NiFi Registry groups to Ranger.

Add NiFi and NiFi Registry groups to Ranger

Provides steps to add the NiFi and NiFi Registry groups in Ranger.

About this task



Note:

If the CFM parcel has been activated on the Base cluster, the nifi and nifi registry groups in Ranger are automatically created and you may skip this task.

If your Compute cluster uses a Shared Data Context that shares the Ranger service, you must create the nifi and nifi registry groups in Ranger on the Base cluster. You must create these groups before you install the NiFi and NiFi Registry service on the Compute cluster, in order for the required NiFi and NiFi Registry Ranger access policies to be created.

Before you begin

- You have created a Shared Data Context.

Procedure

- Go to Ranger.
- Select Settings > Users/Groups/Roles

The **Users/Groups/Roles** page appears.

3. Select the Groups tab, then click Add New Group.
The **Group Detail** page appears.
4. For Group Name, enter nifi. Click Save.
5. Click Add New Group.
6. For Group Name, enter nifiregistry. Click Save.

What to do next

When you have finished creating the Ranger groups, proceed to creating a Compute cluster.

Create Compute cluster

Provides the steps to create a CDP Private Cloud Base Compute cluster.

About this task

You should follow the instructions in the *CDP Installation Guide* for complete information about installing Cloudera Manager and a CDP base cluster. At minimum, you should ensure that you perform the following steps.

Before you begin

- You have prepared your CDP Private Cloud Base Base cluster.
- You have created a Shared Data Context in your Base cluster.
- You have added NiFi and NiFi Registry groups to Ranger in your Base cluster.

Procedure

1. Launch the Add Cluster – Installation wizard.
From your Base cluster detail page, select Add Compute Cluster from the Actions drop-down.

- From the Cluster Basics step, add a cluster name, and select your Shared Data Context from the Data Context drop-down. Click Continue.

Add Cluster - Installation

Cluster Basics

Cluster Name: CFM Compute Cluster

Compute Cluster ↔ **Data Context** ↔ **Base Cluster**

A Compute Cluster consists of only compute nodes. To connect to existing storage, metadata or security services, you must first choose or create a **Data Context** on a Base Cluster. Learn more at [Cloudera SDX Technologies](#).

Data Context: shared-data-context

Data Services: HDFS-1

Metadata Services: None

Security Services: RANGER-1, ATLAS-1

Back Continue

- From the Specify Hosts step, select the hosts you want to belong to your Compute cluster. Click Continue.
- From the Select Repository step, select the CFM parcel. If the CFM parcel has not been added yet, select Parcel Repositories & Network Settings and add the CFM Parcel URL
See *Install the CFM parcel from the repository* for more information.
The CDH parcel is added by default. Click Continue to download, distribute, and activate the CFM and CDH parcels.
- From the Inspect Cluster step, run the Inspect Network Performance and Inspect Hosts inspections. Click Continue to select services to install.

What to do next

When you have finished creating your Compute cluster, proceed by adding NiFi to your Compute cluster.

Add NiFi to the Compute cluster

Provides the steps for adding and configuring the NiFi service to a Compute cluster.

Before you begin

- You have created a Shared Data Context and a Compute cluster.
- You have added the nifi and nifiregistry groups to Ranger in the Base cluster.
- You have created a Compute cluster with CDH and CFM parcels installed.

Procedure

1. After your Compute cluster is created, the Add Cluster - Configuration wizard displays.
2. From the Select Services step, select Custom Services. Select NiFi and click Continue.
3. From the Assign Roles step, select the hosts onto which you want to install your new NiFi roles.

ZooKeeper is a required dependency of NiFi. Select the hosts onto which you want to install ZooKeeper. Click Continue.

4. From the Review Changes step, review changes to your configuration. Provide a value for your Initial Admin Identity. You may choose to further customize your NiFi configurations here.

**Note:**

You must add any group name or identity set by these parameters to Ranger, in order for your installation install to succeed.

- Initial Admin Identity (nifi.initial.admin.identity)
- NiFi proxy group (nifi.proxy.group)
- Initial Admin Groups (nifi.initial.admin.groups)

Click Continue.

5. From the Configure Kerberos step, install Kerberos client libraries on all Compute cluster hosts as needed. Click Continue to initiate the Kerberos enablement.
6. When you have completed these steps, click Continue. This starts the NiFi service installation.
7. Click Continue and Finish to complete the installation.
8. Open a browser and enter the URL to the NiFi UI.

The URL format for the NiFi UI is based on whether or not you selected Knox as a dependency during the installation:

- If you did not select Knox, the URL format is:

```
https://[***HOSTNAME***]:8443/nifi
```

- If you selected Knox, use the Knox URL as a single entry point to securely access all NiFi nodes and switch nodes if one fails. The format is:

```
https://[***KNOX-GATEWAY-HOSTNAME***]:[***KNOX-GATEWAY-PORT***]/gateway/cdp-proxy/nifi-app/nifi/
```

Results

Verify the new services are added properly by checking the health status for the new services. If the Health Status is Good, then the services added properly.

What to do next

When you have finished adding the NiFi service, proceed by creating NiFi node users for NiFi Registry and Ranger.

Create NiFi node users

Provides steps for creating NiFi node users for NiFi Registry and Ranger.

About this task

You must perform this task so that you can save versioned NiFi dataflows to NiFi Registry.

Add users or groups to Ranger

Provides steps to add users or groups to Ranger Policies.

About this task

Determine what the user can command, control, and observe in a NiFi dataflow or in NiFi Registry and accordingly add the user or a group of users to the appropriate pre-defined Ranger access policies.

Each pre-defined Ranger access policy confers specific rights to NiFi or NiFi Registry resources.

For more information, see:

- *Pre-defined Ranger access policies for NiFi resources*
- *Pre-defined Ranger access policies for NiFi Registry resources*


Before you begin

- You have installed Ranger on your Base CDP Private Cloud Base cluster.
- You have added and connected the NiFi and NiFi Registry services.

Procedure


1. From the Base cluster, select Ranger from the list of services. Click Ranger Admin Web UI and log into Ranger.

The **Ranger Service Manager** page displays.



Each cluster in the environment is listed under its respective service. For example, the NiFi clusters in the environment are listed under NiFi.

2. Select a cluster from either the NiFi or NiFi Registry section.
The **List of Policies** page appears.



Ranger Access Manager Audit Security Zone Settings admin

Service Manager Cluster 1_nifi Policies

List of Policies : Cluster 1_nifi

Search for your policy.. Add New Policy

Policy ID	Policy Name	Policy Labels	Status	Audit Logging	Roles	Groups	Users	Action
41	Restricted Components	--	Enabled	Enabled	--	nifi	admin	  
42	Provenance	--	Enabled	Enabled	--	nifi	admin	  
43	Flow	--	Enabled	Enabled	--	nifi	admin	  
44	Tenants	--	Enabled	Enabled	--	nifi	admin	  
45	Controller	--	Enabled	Enabled	--	nifi	admin	  
46	Policies	--	Enabled	Enabled	--	nifi	admin	  
47	Proxies	--	Enabled	Enabled	--	nifi	--	  
48	Root Process Group	--	Enabled	Enabled	--	nifi	admin	  
49	Root Process Group Provenance Data	--	Enabled	Enabled	--	nifi	admin	  
50	Root Process Group Data	--	Enabled	Enabled	--	nifi	admin	  

- Click the ID for a policy.
The **Edit Policy** page appears.

Ranger Access Manager Audit Security Zone Settings admin

Service Manager > Cluster 1_nifi Policies > Edit Policy

Edit Policy

Policy Details :

Policy Type: **Access** Add Validity Period

Policy ID: **43**

Policy Name *: Flow enabled normal

Policy Label: Policy Label

NiFi Resource Identifier *:

Description:

Audit Logging: **YES**

Allow Conditions : hide

Select Role	Select Group	Select User	Permissions	Delegate Admin	
Select Roles	nifi	admin	Read	☐	x
+					

Deny All Other Accesses : **False**

Save **Cancel** **Delete**

- In the Allow Conditions section, add the user or the user group to the Select User field.
- Click Save.

Results

The user now has the NiFi and NiFi Registry rights according to the policies you added the user or user group to. These rights are inherited down the hierarchy unless there is a more specific policy on a component.

What to do next

When you have completed the steps for adding users and groups to Ranger policies, review the steps to deselect unwanted NiFi Registry dependencies and determine whether this task applies to you.

Deselect unwanted NiFi Registry dependencies

Provides steps to remove unwanted NiFi Registry dependencies.

About this task


This is an optional task. During your cluster installation, some dependencies may have been added to NiFi Registry. If you do not want these dependencies, follow these steps to remove them.

Before you begin

- You have installed a CDP Private Cloud Base cluster.
- You have added the NiFi Registry service.

Procedure

1. From Cloudera Manager, click the Clusters tab in the left-hand navigation
2. Click NiFi Registry in the list of services to display the NiFi Registry service page.
3. Select the Configuration tab.
4. Deselect any unwanted dependencies.



The screenshot shows the NiFi Registry Configuration page. On the left, there is a 'Filters' sidebar with sections for SCOPE, CATEGORY, and STATUS. The main area displays a table of services and their dependencies. The 'RANGER Service' is selected, and its dependencies are listed. The 'SDX' dependency is checked, and a blue box highlights the 'NiFi Registry (Service-Wide)' dependency. The 'SDX' checkbox is also checked.

Service	Dependency	Selected
NiFi CA Service Service	NiFi Registry (Service-Wide)	☐
RANGER Service	NiFi Registry (Service-Wide)	☒
KNOX Service	NiFi Registry (Service-Wide)	☐
NiFi Service	NiFi Registry (Service-Wide)	☒
Enable Kerberos Authentication	NiFi Registry (Service-Wide)	☒

5. Click Save Changes. Restart the NiFi Registry service.

What to do next

You have completed your CDP Private Cloud Base installation with NiFi installed on a Compute cluster and NiFi Registry installed on the Base cluster.