

Cloudera Manager 7.11.0

Cloudera Manager Entity Types and Attributes

Date published: 2020-11-30

Date modified: 2023-06-26

CLouDERA

<https://docs.cloudera.com/>

Legal Notice

© Cloudera Inc. 2025. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents

Cloudera Manager Entity Types and Attributes.....	9
Cloudera Manager Entity Types.....	9
CLUSTER.....	9
RACK.....	9
HOST.....	10
ACTIVITY.....	10
ATTEMPT.....	10
CMSERVER.....	11
ROLE.....	11
SERVICE.....	12
NETWORK_INTERFACE.....	12
DISK.....	13
DIRECTORY.....	13
FILESYSTEM.....	14
USER.....	14
IMPALA_QUERY.....	15
YARN_APPLICATION.....	15
HDFS.....	15
NAMENODE.....	16
DATANODE.....	16
SECONDARYNAMENODE.....	17
JOURNALNODE.....	17
HTTPFS.....	18
HDFS-FAILOVERCONTROLLER.....	18
NFSGATEWAY.....	19
HDFS_CACHE_POOL.....	19
HDFS_CACHE_DIRECTIVE.....	19
HBASE.....	20
MASTER.....	20
REGIONSERVER.....	21
HBASETHRIFTSERVER.....	21
HBASERESTSERVER.....	22
HNAMESPACE.....	22
HTABLE.....	23
HREGION.....	23
HBASE_REPLICATION_PEER.....	24
HBASE_REGIONSERVER_REPLICATION_PEER.....	24
MAPREDUCE.....	25
JOBTRACKER.....	25
TASKTRACKER.....	26
MAPREDUCE-FAILOVERCONTROLLER.....	26
MGMT.....	26
AUTH.....	27
AUTHSERVER.....	27
AUTH_LOAD_BALANCER.....	28
ACTIVITYMONITOR.....	28
SERVICEMONITOR.....	29
HOSTMONITOR.....	29
EVENTSERVER.....	30

ALERTPUBLISHER.....	30
REPORTSMANAGER.....	31
NAVIGATOR.....	31
NAVIGATORMETASERVER.....	32
TELEMETRYPUBLISHER.....	32
TIME_SERIES_TABLE.....	32
ZOOKEEPER.....	33
SERVER.....	33
FLUME.....	34
AGENT.....	34
FLUME_SOURCE_TIER.....	35
FLUME_CHANNEL_TIER.....	35
FLUME_SINK_TIER.....	36
FLUME_CHANNEL.....	36
FLUME_SINK.....	37
FLUME_SOURCE.....	37
IMPALA.....	38
IMPALAD.....	38
STATESTORE.....	39
CATALOGSERVER.....	39
LLAMA.....	39
YARN.....	40
RESOURCEMANAGER.....	40
NODEMANAGER.....	41
JOBHISTORY.....	41
YARN_POOL.....	42
YARN_POOL_USER.....	42
IMPALA_POOL.....	43
IMPALA_POOL_USER.....	43
OOZIE.....	44
OOZIE_SERVER.....	44
HIVE.....	44
HIVEMETASTORE.....	45
WEBHCAT.....	45
HIVESERVER2.....	46
HIVE_ON_TEZ.....	46
HIVE_ON_TEZ_HIVESERVER2.....	47
HIVE_EXEC.....	47
HIVE_EXEC_HIVESERVER2.....	48
HIVE_LLAP.....	48
LLAPPROXY.....	49
HIVE_LLAP_HIVESERVER2.....	49
HUE.....	50
HUE_SERVER.....	50
KT_RENEWER.....	51
HUE_LOAD_BALANCER.....	51
SENTRY.....	51
SENTRY_SERVER.....	52
SQOOP.....	52
SQOOP_SERVER.....	53
SOLR.....	53
SOLR_SERVER.....	54
SOLR_COLLECTION.....	54
SOLR_SHARD.....	55
SOLR_REPLICA.....	55
KS_INDEXER.....	56

HBASE_INDEXER.....	56
CORE_SETTINGS.....	57
ECS.....	57
ECS_SERVER.....	57
ECS_AGENT.....	58
DOCKER.....	58
DOCKER_SERVER.....	59
ACCUMULO16.....	59
RANGER_RMS.....	60
ACCUMULO_C6.....	60
STREAMS_REPLICATION_MANAGER.....	61
TEZ.....	61
LUNA_KMS.....	62
PROFILER_SCHEDULER.....	62
SPARK3_ON_YARN.....	63
RANGER_KMS.....	63
ATLAS.....	64
QUEUEMANAGER.....	64
KUDU.....	64
CRUISE_CONTROL.....	65
SCHEMAREGISTRY.....	65
OMID.....	66
SPARK_ON_YARN.....	66
LIVY.....	67
THALES_KMS.....	67
PHOENIX.....	68
RANGER_KMS_KTS.....	68
ISILON.....	69
RANGER_RAZ.....	69
KNOX.....	70
RANGER.....	70
KMS.....	70
ZEPPELIN.....	71
STREAMS_MESSAGING_MANAGER.....	71
KEYTRUSTEE.....	72
DAS.....	72
KEYTRUSTEE_SERVER.....	73
OZONE.....	73
QUERY_PROCESSOR.....	74
KAFKA.....	74
LIVY_FOR_SPARK3.....	75
SQL_STREAM_BUILDER.....	75
PROFILER_MANAGER.....	76
FLINK.....	76
SPARK3_ON_YARN-SPARK3_YARN_HISTORY_SERVER.....	77
PHOENIX-PHOENIX_QUERY_SERVER.....	77
QUERY_PROCESSOR-QUERY_PROCESSOR.....	77
RANGER_RAZ-RANGER_RAZ_SERVER.....	78
KAFKA-KAFKA_BROKER.....	78
KAFKA-KAFKA_MIRROR_MAKER.....	79
KAFKA-KAFKA_CONNECT.....	79
CRUISE_CONTROL-CRUISE_CONTROL_SERVER.....	80
STREAMS_MESSAGING_MANAGER-STREAMS_MESSAGING_MANAGER_SERVER.....	80
STREAMS_MESSAGING_MANAGER-STREAMS_MESSAGING_MANAGER_UI.....	81
LIVY-LIVY_SERVER.....	81
OZONE-STORAGE_CONTAINER_MANAGER.....	82

OZONE-OZONE_MANAGER.....	82
OZONE-OZONE_RECON.....	83
OZONE-OZONE_DATANODE.....	83
OZONE-S3_GATEWAY.....	84
OZONE-OZONE_PROMETHEUS.....	84
RANGER_RMS-RANGER_RMS_SERVER.....	85
RANGER-RANGER_ADMIN.....	85
RANGER-RANGER_USERSYNC.....	85
RANGER-RANGER_TAGSYNC.....	86
OMID-OMID_TSO.....	86
KUDU-KUDU_MASTER.....	87
KUDU-KUDU_TSERVER.....	87
STREAMS_REPLICATION_MANAGER- STREAMS_REPLICATION_MANAGER_DRIVER.....	88
STREAMS_REPLICATION_MANAGER- STREAMS_REPLICATION_MANAGER_SERVICE.....	88
KNOX-KNOX_GATEWAY.....	89
KNOX-IDBROKER.....	89
QUEUEMANAGER-QUEUEMANAGER_WEBAPP.....	90
QUEUEMANAGER-QUEUEMANAGER_STORE.....	90
ATLAS-ATLAS_SERVER.....	91
SPARK_ON_YARN-SPARK_YARN_HISTORY_SERVER.....	91
SCHEMAREGISTRY-SCHEMA_REGISTRY_SERVER.....	92
LIVY_FOR_SPARK3-LIVY_SERVER_FOR_SPARK3.....	92
RANGER_KMS_KTS-RANGER_KMS_SERVER_KTS.....	93
ZEPPELIN-ZEPPELIN_SERVER.....	93
LUNA_KMS-HSMKP_LUNA.....	93
LUNA_KMS-HSMKP_METASTORE_LUNA.....	94
RANGER_KMS-RANGER_KMS_SERVER.....	94
DAS-DAS_WEBAPP.....	95
DAS-DAS_EVENT_PROCESSOR.....	95
KMS-KMS.....	96
PROFILER_SCHEDULER-PROFILER_SCHEDULER_AGENT.....	96
ACCUMULO16-ACCUMULO16_MASTER.....	97
ACCUMULO16-ACCUMULO16_TSERVER.....	97
ACCUMULO16-ACCUMULO16_GC.....	98
ACCUMULO16-ACCUMULO16_MONITOR.....	98
ACCUMULO16-ACCUMULO16_TRACER.....	99
PROFILER_MANAGER-PROFILER_ADMIN_AGENT.....	99
PROFILER_MANAGER-DATA_DISCOVERY_SERVICE_AGENT.....	100
PROFILER_MANAGER-PROFILER_METRICS_AGENT.....	100
KEYTRUSTEE_SERVER-KEYTRUSTEE_ACTIVE_SERVER.....	101
KEYTRUSTEE_SERVER-KEYTRUSTEE_PASSIVE_SERVER.....	101
KEYTRUSTEE_SERVER-DB_ACTIVE.....	101
KEYTRUSTEE_SERVER-DB_PASSIVE.....	102
THALES_KMS-HSMKP_THALES.....	102
THALES_KMS-HSMKP_METASTORE_THALES.....	103
FLINK-FLINK_HISTORY_SERVER.....	103
KEYTRUSTEE-KMS_KEYTRUSTEE.....	104
ACCUMULO_C6-ACCUMULO_MASTER.....	104
ACCUMULO_C6-ACCUMULO_TSERVER.....	105
ACCUMULO_C6-ACCUMULO_GC.....	105
ACCUMULO_C6-ACCUMULO_MONITOR.....	106
ACCUMULO_C6-ACCUMULO_TRACER.....	106
SQL_STREAM_BUILDER-STREAMING_SQL_ENGINE.....	107
SQL_STREAM_BUILDER-MATERIALIZED_VIEW_ENGINE.....	107

SQL_STREAM_BUILDER-STREAMING_SQL_CONSOLE.....	108
KAFKA_BROKER_LOG_DIRECTORY.....	108
KAFKA_TOPIC.....	109
KAFKA_BROKER_TOPIC.....	109
KAFKA_REPLICA.....	109
KAFKA_BROKER_TOPIC_PARTITION.....	110
KAFKA_PRODUCER.....	110
KAFKA_CONSUMER_GROUP.....	111
KAFKA_CONNECT_CONNECTOR_TASK_METRICS.....	111
KAFKA_CONNECT_CONNECTOR_SINK_TASK_METRICS.....	112
KAFKA_CONNECT_CONNECTOR_SOURCE_TASK_METRICS.....	112
KAFKA_CONNECT_CONNECTOR_TASK_ERROR_METRICS.....	113
KUDU_TABLE.....	113
KUDU_TABLET.....	114
KUDU_REPLICA.....	114
STREAMS_REPLICATION_MANAGER_HERDER.....	115
IMPALA_DAEMON_POOL.....	115
HIVE_ON_TEZ_TABLE.....	116
Cloudera Manager Entity Type Attributes.....	116
entityName.....	116
category.....	116
version.....	116
active.....	117
roleName.....	117
roleType.....	117
roleState.....	117
roleConfigGroup.....	117
serviceName.....	118
serviceDisplayName.....	118
serviceType.....	118
serviceState.....	118
userName.....	118
groupName.....	118
ownerName.....	119
queueName.....	119
poolName.....	119
path.....	119
expired.....	119
clusterId.....	120
clusterName.....	120
clusterDisplayName.....	120
rackId.....	120
hostId.....	120
hostname.....	121
interface.....	121
device.....	121
logicalPartition.....	121
partition.....	121
mountpoint.....	121
mountOptions.....	122
filesystemType.....	122
nameserviceName.....	122
cacheId.....	122
hnamespaceName.....	122
htableName.....	123
systemTable.....	123

hregionName.....	123
hbaseReplicationPeerId.....	123
hbaseReplicationPeerClusterKey.....	123
timeSeriesTableName.....	123
timeSeriesApplicationName.....	124
rollup.....	124
agentName.....	124
componentName.....	124
schedulerType.....	124
solrCollectionName.....	125
solrShardName.....	125
solrReplicaName.....	125
kafkaBrokerId.....	125
kafkaClientId.....	125
kafkaConnectConnectorName.....	126
kafkaConnectConnectorTaskId.....	126
kafkaConsumerGroup.....	126
kafkaInternalTopic.....	126
kafkaLogDirectoryPath.....	126
kafkaPartitionId.....	126
kafkaTopicName.....	127
kuduTableId.....	127
kuduTableName.....	127
kuduTableState.....	127
kuduTableId.....	127
kuduTableState.....	128
streams_replication_manager_herder_name.....	128
hive_on_tezTableName.....	128

Cloudera Manager Entity Types and Attributes

Cloudera Manager Entity Types

CLUSTER

Category	CLUSTER
Name For Cross Entity Aggregate Metrics	clusters
Display Name	Cluster
Description	A Cloudera Manager cluster. Called 'CLUSTER' in queries.
Immutable Attribute Names	clusterName, clusterId
Mutable Attribute Names	clusterDisplayName, version
Entity Name Format	clusterId
Entity Display Name Format	null
Parent Metric Entity Type Names	

RACK

Category	RACK
Name For Cross Entity Aggregate Metrics	racks
Display Name	Rack
Description	A rack. Called 'RACK' in queries.
Immutable Attribute Names	rackId
Mutable Attribute Names	
Entity Name Format	rackId
Entity Display Name Format	null

Parent Metric Entity Type Names**HOST****Category**

HOST

Name For Cross Entity Aggregate Metrics

hosts

Display Name

Host

Description

A Cloudera Manager host. Called 'HOST' in queries.

Immutable Attribute Names

clusterName, hostId, clusterId, rackId

Mutable Attribute Names

hostname

Entity Name Format

hostId

Entity Display Name Format

null

Parent Metric Entity Type Names

RACK, CLUSTER

ACTIVITY**Category**

ACTIVITY

Name For Cross Entity Aggregate Metrics

activities

Display Name

Activity

Description

A MapReduce MR1-based activity. Examples include MapReduce jobs, Hive queries, and Oozie workflows. Called 'ACTIVITY' in queries.

Immutable Attribute Names**Mutable Attribute Names****Entity Name Format****Entity Display Name Format**

null

Parent Metric Entity Type Names**ATTEMPT****Category**

ATTEMPT

Name For Cross Entity Aggregate Metrics

attempts

Display Name

Attempt

Description

A MapReduce MR1-based attempt. Examples include MapReduce map and reduce tasks. Called 'ATTEMPT' in queries.

Immutable Attribute Names**Mutable Attribute Names****Entity Name Format****Entity Display Name Format**

null

Parent Metric Entity Type Names**CMSEVER****Category**

CMSEVER

Name For Cross Entity Aggregate Metrics

cmservers

Display Name

Cloudera Manager Server

Description

The Cloudera Manager Server. Called 'CMSEVER' in queries.

Immutable Attribute Names

hostname, entityName, category

Mutable Attribute Names**Entity Name Format**

entityName, hostname

Entity Display Name Format

null

Parent Metric Entity Type Names**ROLE****Category**

ROLE

Name For Cross Entity Aggregate Metrics

roles

Display Name

Role

Description

The {0} role. Called "{1}" in queries. Called 'ROLE' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, hostId, roleName, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names**SERVICE****Category**

SERVICE

Name For Cross Entity Aggregate Metrics

services

Display Name

Service

Description

The {0} service. Called "{1}" in queries. Called 'SERVICE' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names**NETWORK_INTERFACE****Category**

NETWORK_INTERFACE

Name For Cross Entity Aggregate Metrics

network_interfaces

Display Name

Network Interface

Description

A network interface on a Cloudera Manager host. Called 'NETWORK_INTERFACE' in queries.

Immutable Attribute Names

clusterName, hostId, clusterId, rackId, interface

Mutable Attribute Names**Entity Name Format**

hostId, interface

Entity Display Name Format

null

Parent Metric Entity Type Names

HOST

DISK**Category**

DISK

Name For Cross Entity Aggregate Metrics

disks

Display Name

Disk

Description

A disk device or disk partition on a Cloudera Manager host. Both disk devices and disk partitions are modeled using this type. The 'logicalPartition' attribute can be used to distinguish a disk device and a disk partition. Called 'DISK' in queries.

Immutable Attribute Names

clusterName, logicalPartition, hostId, clusterId, rackId, device

Mutable Attribute Names**Entity Name Format**

hostId, device

Entity Display Name Format

null

Parent Metric Entity Type Names

HOST

DIRECTORY**Category**

DIRECTORY

Name For Cross Entity Aggregate Metrics

directories

Display Name

Directory

Description

A monitored directory on a Cloudera Manager host. Cloudera Manager only monitors those directories on a host that it knows are being written to a role or the Cloudera Manager component. Called 'DIRECTORY' in queries.

Immutable Attribute Names

path, serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names**Entity Name Format**

hostId, roleName, path

Entity Display Name Format

null

Parent Metric Entity Type Names

HOST, ROLE

FILESYSTEM**Category**

FILESYSTEM

Name For Cross Entity Aggregate Metrics

filesystems

Display Name

Filesystem

Description

A filesystem on a Cloudera Manager host. By default, Cloudera Manager only monitors local (non-nodev) filesystems and a small set of nodev filesystems (e.g. nfs, nfs4, tmpfs). You can change the monitored filesystem types through the Cloudera Manager Agent config.ini settings. Called 'FILESYSTEM' in queries.

Immutable Attribute Names

clusterName, hostId, clusterId, rackId, mountpoint

Mutable Attribute Names

partition, mountOptions, filesystemType

Entity Name Format

hostId, mountpoint

Entity Display Name Format

null

Parent Metric Entity Type Names

HOST

USER**Category**

USER

Name For Cross Entity Aggregate Metrics

users

Display Name

User

Description

A user. Called 'USER' in queries.

Immutable Attribute Names

userName

Mutable Attribute Names**Entity Name Format**

userName

Entity Display Name Format

null

Parent Metric Entity Type Names

IMPALA_QUERY

Category	IMPALA_QUERY
Name For Cross Entity Aggregate Metrics	impala_queries
Display Name	Impala Query
Description	An Impala query. Called 'IMPALA_QUERY' in queries.
Immutable Attribute Names	
Mutable Attribute Names	
Entity Name Format	
Entity Display Name Format	null
Parent Metric Entity Type Names	

YARN_APPLICATION

Category	YARN_APPLICATION
Name For Cross Entity Aggregate Metrics	yarn_applications
Display Name	YARN Application
Description	A YARN application. Called 'YARN_APPLICATION' in queries.
Immutable Attribute Names	
Mutable Attribute Names	
Entity Name Format	
Entity Display Name Format	null
Parent Metric Entity Type Names	

HDFS

Category	SERVICE
Name For Cross Entity Aggregate Metrics	hdfss
Display Name	HDFS
Description	The HDFS service. Called 'HDFS' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

NAMENODE**Category**

ROLE

Name For Cross Entity Aggregate Metrics

namenodes

Display Name

NameNode

Description

The NameNode role. Called 'NAMENODE' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HDFS, RACK

DATANODE**Category**

ROLE

Name For Cross Entity Aggregate Metrics

datanodes

Display Name

DataNode

Description

The DataNode role. Called 'DATANODE' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
HDFS, RACK

SECONDARYNAMENODE

Category
ROLE

Name For Cross Entity Aggregate Metrics
secondarynamenodes

Display Name
SecondaryNameNode

Description
The SecondaryNameNode role. Called 'SECONDARYNAMENODE' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
HDFS, RACK

JOURNALNODE

Category
ROLE

Name For Cross Entity Aggregate Metrics
journalnodes

Display Name
JournalNode

Description
The JournalNode role. Called 'JOURNALNODE' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HDFS, RACK

HTTPFS**Category**

ROLE

Name For Cross Entity Aggregate Metrics

httpfss

Display Name

HttpFS

Description

The HttpFS role. Called 'HTTPFS' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HDFS, RACK

HDFS-FAILOVERCONTROLLER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hdfs_failovercontrollers

Display Name

Failover Controller

Description

The Failover Controller role. Called 'HDFS-FAILOVERCONTROLLER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HDFS, RACK

NFSGATEWAY**Category**

ROLE

Name For Cross Entity Aggregate Metrics

nfsgateways

Display Name

NFS Gateway

Description

The NFS Gateway role. Called 'NFSGATEWAY' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HDFS, RACK

HDFS_CACHE_POOL**Category**

HDFS_CACHE_POOL

Name For Cross Entity Aggregate Metrics

hdfs_cache_pools

Display Name

HDFS Cache Pool

Description

An HDFS cache pool. Called 'HDFS_CACHE_POOL' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, nameserviceName, clusterId, poolName

Mutable Attribute Names

groupName, ownerName

Entity Name Format

serviceName, nameserviceName, poolName

Entity Display Name Format

null

Parent Metric Entity Type Names

HDFS

HDFS_CACHE_DIRECTIVE**Category**

HDFS_CACHE_DIRECTIVE
Name For Cross Entity Aggregate Metrics
hdfs_cache_directives
Display Name
HDFS Cache Directive
Description
An HDFS cache directive. Called 'HDFS_CACHE_DIRECTIVE' in queries.
Immutable Attribute Names
path, serviceType, serviceName, clusterName, nameserviceName, clusterId, cacheId
Mutable Attribute Names
poolName, expired
Entity Name Format
serviceName, nameserviceName, cacheId
Entity Display Name Format
null
Parent Metric Entity Type Names
HDFS_CACHE_POOL

HBASE

Category
SERVICE
Name For Cross Entity Aggregate Metrics
hbases
Display Name
HBase
Description
The HBase service. Called 'HBASE' in queries.
Immutable Attribute Names
serviceType, serviceName, clusterName, clusterId
Mutable Attribute Names
serviceDisplayName
Entity Name Format
serviceName
Entity Display Name Format
null
Parent Metric Entity Type Names
CLUSTER

MASTER

Category
ROLE
Name For Cross Entity Aggregate Metrics
masters

Display Name

Master

Description

The Master role. Called 'MASTER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HBASE, RACK

REGIONSERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

regionservers

Display Name

RegionServer

Description

The RegionServer role. Called 'REGIONSERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HBASE, RACK

HBASETHRIFTSERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hbasethriftservers

Display Name

HBase Thrift Server

Description

The HBase Thrift Server role. Called 'HBASETHRIFTSERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HBASE, RACK

HBASERESTSERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hbaserestservers

Display Name

HBase REST Server

Description

The HBase REST Server role. Called 'HBASERESTSERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HBASE, RACK

HNAMESPACE**Category**

HNAMESPACE

Name For Cross Entity Aggregate Metrics

hnamespaces

Display Name

HNamespace

Description

An HBase namespace. Called 'HNAMESPACE' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId, hnamespaceName

Mutable Attribute Names**Entity Name Format**

serviceName, hnamespaceName

Entity Display Name Format

null

Parent Metric Entity Type Names

HBASE

HTABLE**Category**

HTABLE

Name For Cross Entity Aggregate Metrics

htables

Display Name

HTable

Description

An HBase table. Called 'HTABLE' in queries.

Immutable Attribute Names

serviceType, serviceName, systemTable, clusterName, clusterId, htableName, hnamespaceName

Mutable Attribute Names**Entity Name Format**

serviceName, htableName

Entity Display Name Format

null

Parent Metric Entity Type Names

HNAMESPACE, HBASE

HREGION**Category**

HREGION

Name For Cross Entity Aggregate Metrics

hregions

Display Name

HRegion

Description

An HBase region. Called 'HREGION' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, systemTable, clusterName, hregionName, hregionStartTimeMs, clusterId, htableName, hnamespaceName

Mutable Attribute Names

roleName, hostId, hostname, rackId

Entity Name Format

serviceName, hregionName

Entity Display Name Format

null

Parent Metric Entity Type Names

HTABLE, REGIONSERVER

HBASE_REPLICATION_PEER**Category**

HBASE_REPLICATION_PEER

Name For Cross Entity Aggregate Metrics

hbase_replication_peers

Display Name

HBase Replication Peer

Description

An HBase replication peer. This is a target cluster for replications from this HBase cluster. Called 'HBASE_REPLICATION_PEER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId, hbaseReplicationPeerId

Mutable Attribute Names

hbaseReplicationPeerClusterKey

Entity Name Format

serviceName, hbaseReplicationPeerId

Entity Display Name Format

null

Parent Metric Entity Type Names

HBASE

HBASE_REGIONSERVER_REPLICATION_PEER**Category**

HBASE_REGIONSERVER_REPLICATION_PEER

Name For Cross Entity Aggregate Metrics

hbase_regionserver_replication_peers

Display Name

HBase RegionServer Replication Peer

Description

An HBase RegionServer replication peer. This represents replication done from a RegionServer to a replication peer. Called 'HBASE_REGIONSERVER_REPLICATION_PEER' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, hostname, clusterName, hostId, roleName, clusterId, hbaseReplicationPeerId, rackId

Mutable Attribute Names**Entity Name Format**

roleName, hbaseReplicationPeerId

Entity Display Name Format

null

Parent Metric Entity Type Names

REGIONSERVER, HBASE_REPLICATION_PEER

MAPREDUCE**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

mapreduces

Display Name

MapReduce

Description

The MapReduce service. Called 'MAPREDUCE' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

JOBTRACKER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

jobtrackers

Display Name

JobTracker

Description

The JobTracker role. Called 'JOBTRACKER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

MAPREDUCE, RACK

TASKTRACKER

Category	ROLE
Name For Cross Entity Aggregate Metrics	tasktrackers
Display Name	TaskTracker
Description	The TaskTracker role. Called 'TASKTRACKER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	MAPREDUCE, RACK

MAPREDUCE-FAILOVERCONTROLLER

Category	ROLE
Name For Cross Entity Aggregate Metrics	mapreduce_failovercontrollers
Display Name	Failover Controller
Description	The Failover Controller role. Called 'MAPREDUCE-FAILOVERCONTROLLER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	MAPREDUCE, RACK

MGMT

Category	SERVICE
-----------------	---------

Name For Cross Entity Aggregate Metrics

mgmts

Display Name

Cloudera Management Service

Description

The Cloudera Management Service service. Called 'MGMT' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterId

Mutable Attribute Names

version, serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names**AUTH****Category**

SERVICE

Name For Cross Entity Aggregate Metrics

auths

Display Name

Authentication Service

Description

The Authentication Service service. Called 'AUTH' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterId

Mutable Attribute Names

version, serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names**AUTHSERVER****Category**

ROLE

Name For Cross Entity Aggregate Metrics

authservers

Display Name

Authentication Server

Description

The Authentication Server role. Called 'AUTHSERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

AUTH, RACK

AUTH_LOAD_BALANCER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

auth_load_balancers

Display Name

Authentication Server Load Balancer

Description

The Authentication Server Load Balancer role. Called 'AUTH_LOAD_BALANCER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

AUTH, RACK

ACTIVITYMONITOR**Category**

ROLE

Name For Cross Entity Aggregate Metrics

activitymonitors

Display Name

Activity Monitor - Unsupported Since 7.0.0

Description

The Activity Monitor - Unsupported Since 7.0.0 role. Called 'ACTIVITYMONITOR' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

MGMT, RACK

SERVICEMONITOR**Category**

ROLE

Name For Cross Entity Aggregate Metrics

servicemonitors

Display Name

Service Monitor

Description

The Service Monitor role. Called 'SERVICEMONITOR' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

MGMT, RACK

HOSTMONITOR**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hostmonitors

Display Name

Host Monitor

Description

The Host Monitor role. Called 'HOSTMONITOR' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
MGMT, RACK

EVENTSERVER

Category
ROLE

Name For Cross Entity Aggregate Metrics
eventservers

Display Name
Event Server

Description
The Event Server role. Called 'EVENTSERVER' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
MGMT, RACK

ALERTPUBLISHER

Category
ROLE

Name For Cross Entity Aggregate Metrics
alertpublishers

Display Name
Alert Publisher

Description
The Alert Publisher role. Called 'ALERTPUBLISHER' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names

MGMT, RACK

REPORTSMANAGER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

reportsmanagers

Display Name

Reports Manager

Description

The Reports Manager role. Called 'REPORTSMANAGER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

MGMT, RACK

NAVIGATOR**Category**

ROLE

Name For Cross Entity Aggregate Metrics

navigators

Display Name

Navigator Audit Server

Description

The Navigator Audit Server role. Called 'NAVIGATOR' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

MGMT, RACK

NAVIGATORMETASERVER

Category	ROLE
Name For Cross Entity Aggregate Metrics	navigatormetaservers
Display Name	Navigator Metadata Server
Description	The Navigator Metadata Server role. Called 'NAVIGATORMETASERVER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	MGMT, RACK

TELEMETRYPUBLISHER

Category	ROLE
Name For Cross Entity Aggregate Metrics	telemetrypublishers
Display Name	Telemetry Publisher
Description	The Telemetry Publisher role. Called 'TELEMETRYPUBLISHER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	MGMT, RACK

TIME_SERIES_TABLE

Category	TIME_SERIES_TABLE
-----------------	-------------------

Name For Cross Entity Aggregate Metrics

time_series_tables

Display Name

Time Series Table

Description

A table within the Cloudera Manager Host Monitor or Cloudera Manager Service Monitor storage system. Called 'TIME_SERIES_TABLE' in queries.

Immutable Attribute Names

timeSeriesTableName, rollup, roleType, timeSeriesApplicationName, hostId, roleName

Mutable Attribute Names

path, hostname

Entity Name Format

roleName, timeSeriesTableName

Entity Display Name Format

null

Parent Metric Entity Type Names**ZOOKEEPER****Category**

SERVICE

Name For Cross Entity Aggregate Metrics

zookeepers

Display Name

ZooKeeper

Description

The ZooKeeper service. Called 'ZOOKEEPER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

servers

Display Name

Server

Description

The Server role. Called 'SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ZOOKEEPER, RACK

FLUME**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

flumes

Display Name

Flume

Description

The Flume service. Called 'FLUME' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

AGENT**Category**

ROLE

Name For Cross Entity Aggregate Metrics

agents

Display Name

Agent

Description

The Agent role. Called 'AGENT' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

agentName, roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

FLUME, RACK

FLUME_SOURCE_TIER**Category**

FLUME_SOURCE_TIER

Name For Cross Entity Aggregate Metrics

flume_source_tiers

Display Name

Flume Source Tier

Description

A Flume source tier is an aggregation point for all Flume sources using the same agent name and source name. Called 'FLUME_SOURCE_TIER' in queries.

Immutable Attribute Names

serviceType, serviceName, componentName, agentName, clusterName, clusterId

Mutable Attribute Names**Entity Name Format**

serviceName, agentName, componentName

Entity Display Name Format

null

Parent Metric Entity Type Names

FLUME

FLUME_CHANNEL_TIER**Category**

FLUME_CHANNEL_TIER

Name For Cross Entity Aggregate Metrics

flume_channel_tiers

Display Name

Flume Channel Tier

Description

A Flume channel tier is an aggregation point for all Flume channels using the same agent name and channel name. Called 'FLUME_CHANNEL_TIER' in queries.

Immutable Attribute Names

serviceType, serviceName, componentName, agentName, clusterName, clusterId

Mutable Attribute Names**Entity Name Format**

serviceName, agentName, componentName

Entity Display Name Format

null

Parent Metric Entity Type Names

FLUME

FLUME_SINK_TIER**Category**

FLUME_SINK_TIER

Name For Cross Entity Aggregate Metrics

flume_sink_tiers

Display Name

Flume Sink Tier

Description

A Flume sink tier is an aggregation point for all Flume sinks using the same agent name and sink name. Called 'FLUME_SINK_TIER' in queries.

Immutable Attribute Names

serviceType, serviceName, componentName, agentName, clusterName, clusterId

Mutable Attribute Names**Entity Name Format**

serviceName, agentName, componentName

Entity Display Name Format

null

Parent Metric Entity Type Names

FLUME

FLUME_CHANNEL**Category**

FLUME_CHANNEL

Name For Cross Entity Aggregate Metrics

flume_channels

Display Name

Flume Channel

Description

A Flume channel. Called 'FLUME_CHANNEL' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, componentName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

agentName, hostname

Entity Name Format

roleName, componentName

Entity Display Name Format

null

Parent Metric Entity Type Names

AGENT, FLUME_CHANNEL_TIER

FLUME_SINK

Category

FLUME_SINK

Name For Cross Entity Aggregate Metrics

flume_sinks

Display Name

Flume Sink

Description

A Flume sink. Called 'FLUME_SINK' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, componentName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

agentName, hostname

Entity Name Format

roleName, componentName

Entity Display Name Format

null

Parent Metric Entity Type Names

AGENT, FLUME_SINK_TIER

FLUME_SOURCE

Category

FLUME_SOURCE

Name For Cross Entity Aggregate Metrics

flume_sources

Display Name

Flume Source

Description

A Flume source. Called 'FLUME_SOURCE' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, componentName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

agentName, hostname

Entity Name Format

roleName, componentName

Entity Display Name Format

null

Parent Metric Entity Type Names

AGENT, FLUME_SOURCE_TIER

IMPALA**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

impalas

Display Name

Impala

Description

The Impala service. Called 'IMPALA' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

IMPALAD**Category**

ROLE

Name For Cross Entity Aggregate Metrics

impalads

Display Name

Impala Daemon

Description

The Impala Daemon role. Called 'IMPALAD' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

IMPALA, RACK

STATESTORE

Category	ROLE
Name For Cross Entity Aggregate Metrics	statestores
Display Name	Impala StateStore
Description	The Impala StateStore role. Called 'STATESTORE' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	IMPALA, RACK

CATALOGSERVER

Category	ROLE
Name For Cross Entity Aggregate Metrics	catalogservers
Display Name	Impala Catalog Server
Description	The Impala Catalog Server role. Called 'CATALOGSERVER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	IMPALA, RACK

LLAMA

Category	ROLE
-----------------	------

Name For Cross Entity Aggregate Metrics

llamas

Display Name

Impala Llama ApplicationMaster

Description

The Impala Llama ApplicationMaster role. Called 'LLAMA' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

IMPALA, RACK

YARN**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

yarns

Display Name

YARN

Description

The YARN service. Called 'YARN' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

RESOURCEMANAGER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

resourcemangers

Display Name

ResourceManager

Description

The ResourceManager role. Called 'RESOURCEMANAGER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

YARN, RACK

NODEMANAGER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

nodemanagers

Display Name

NodeManager

Description

The NodeManager role. Called 'NODEMANAGER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

YARN, RACK

JOBHISTORY**Category**

ROLE

Name For Cross Entity Aggregate Metrics

jobhistorys

Display Name

JobHistory Server

Description

The JobHistory Server role. Called 'JOBHISTORY' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

YARN, RACK

YARN_POOL**Category**

YARN_POOL

Name For Cross Entity Aggregate Metrics

yarn_pools

Display Name

YARN Pool

Description

A YARN pool. Within YARN, a pool is referred to as a queue. Called 'YARN_POOL' in queries.

Immutable Attribute Names

serviceType, serviceName, queueName, clusterName, clusterId, poolName

Mutable Attribute Names

schedulerType

Entity Name Format

serviceName, poolName

Entity Display Name Format

null

Parent Metric Entity Type Names

YARN

YARN_POOL_USER**Category**

YARN_POOL_USER

Name For Cross Entity Aggregate Metrics

yarn_pool_users

Display Name

YARN Pool User

Description

A YARN pool user. Called 'YARN_POOL_USER' in queries.

Immutable Attribute Names

serviceType, serviceName, queueName, clusterName, clusterId, poolName, userName

Mutable Attribute Names

Entity Name Format

serviceName, poolName, userName

Entity Display Name Format

null

Parent Metric Entity Type Names

YARN_POOL

IMPALA_POOL**Category**

IMPALA_POOL

Name For Cross Entity Aggregate Metrics

impala_pools

Display Name

Impala Pool

Description

An Impala pool. Called 'IMPALA_POOL' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId, poolName

Mutable Attribute Names**Entity Name Format**

serviceName, poolName

Entity Display Name Format

null

Parent Metric Entity Type Names

IMPALA

IMPALA_POOL_USER**Category**

IMPALA_POOL_USER

Name For Cross Entity Aggregate Metrics

impala_pool_users

Display Name

Impala Pool User

Description

An Impala pool user. Called 'IMPALA_POOL_USER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId, poolName, userName

Mutable Attribute Names**Entity Name Format**

serviceName, poolName, userName

Entity Display Name Format

null

Parent Metric Entity Type Names

IMPALA_POOL

OOZIE

Category

SERVICE

Name For Cross Entity Aggregate Metrics

oozies

Display Name

Oozie

Description

The Oozie service. Called 'OOZIE' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

OOZIE_SERVER

Category

ROLE

Name For Cross Entity Aggregate Metrics

oozie_servers

Display Name

Oozie Server

Description

The Oozie Server role. Called 'OOZIE_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

OOZIE, RACK

HIVE

Category

Category	SERVICE
Name For Cross Entity Aggregate Metrics	hives
Display Name	Hive
Description	The Hive service. Called 'HIVE' in queries.
Immutable Attribute Names	serviceType, serviceName, clusterName, clusterId
Mutable Attribute Names	serviceDisplayName
Entity Name Format	serviceName
Entity Display Name Format	null
Parent Metric Entity Type Names	CLUSTER

HIVEMETASTORE

Category	ROLE
Name For Cross Entity Aggregate Metrics	hivemetastores
Display Name	Hive Metastore Server
Description	The Hive Metastore Server role. Called 'HIVEMETASTORE' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	HIVE, RACK

WEBHCAT

Category	ROLE
Name For Cross Entity Aggregate Metrics	webhcats

Display Name

WebHCat Server

Description

The WebHCat Server role. Called 'WEBHCAT' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HIVE, RACK

HIVESERVER2**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hiveserver2s

Display Name

HiveServer2

Description

The HiveServer2 role. Called 'HIVESERVER2' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HIVE, RACK

HIVE_ON_TEZ**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

hive_on_tezs

Display Name

Hive on Tez

Description

The Hive on Tez service. Called 'HIVE_ON_TEZ' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

HIVE_ON_TEZ_HIVESERVER2**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hive_on_tez_hiveserver2s

Display Name

HiveServer2

Description

The HiveServer2 role. Called 'HIVE_ON_TEZ_HIVESERVER2' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HIVE_ON_TEZ, RACK

HIVE_EXEC**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

hive_execs

Display Name

Hive Execution

Description

The Hive Execution service. Called 'HIVE_EXEC' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

HIVE_EXEC_HIVESERVER2**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hive_exec_hiveserver2s

Display Name

HiveServer2

Description

The HiveServer2 role. Called 'HIVE_EXEC_HIVESERVER2' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HIVE_EXEC, RACK

HIVE_LLAP**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

hive_llaps

Display Name

Hive LLAP

Description

The Hive LLAP service. Called 'HIVE_LLAP' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format
null

Parent Metric Entity Type Names
CLUSTER

LLAPPROXY

Category
ROLE

Name For Cross Entity Aggregate Metrics
llapproxys

Display Name
LLAP Proxy

Description
The LLAP Proxy role. Called 'LLAPPROXY' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
HIVE_LLAP, RACK

HIVE_LLAP_HIVESERVER2

Category
ROLE

Name For Cross Entity Aggregate Metrics
hive_llap_hiveserver2s

Display Name
HiveServer2

Description
The HiveServer2 role. Called 'HIVE_LLAP_HIVESERVER2' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names

HIVE_LLAP, RACK

HUE**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

hues

Display Name

Hue

Description

The Hue service. Called 'HUE' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

HUE_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hue_servers

Display Name

Hue Server

Description

The Hue Server role. Called 'HUE_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HUE, RACK

KT_RENEWER

Category

ROLE

Name For Cross Entity Aggregate Metrics

kt_renewers

Display Name

Kerberos Ticket Renewer

Description

The Kerberos Ticket Renewer role. Called 'KT_RENEWER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HUE, RACK

HUE_LOAD_BALANCER

Category

ROLE

Name For Cross Entity Aggregate Metrics

hue_load_balancers

Display Name

Load Balancer

Description

The Load Balancer role. Called 'HUE_LOAD_BALANCER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

HUE, RACK

SENTRY

Category

SERVICE

Name For Cross Entity Aggregate Metrics

sentrys

Display Name

Sentry

Description

The Sentry service. Called 'SENTRY' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

SENTRY_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

sentry_servers

Display Name

Sentry Server

Description

The Sentry Server role. Called 'SENTRY_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

SENTRY, RACK

SQOOP**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

sqoops

Display Name

Sqoop 2

Description

The Sqoop 2 service. Called 'SQOOP' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

SQOOP_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

sqoop_servers

Display Name

Sqoop 2 Server

Description

The Sqoop 2 Server role. Called 'SQOOP_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

SQOOP, RACK

SOLR**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

solrs

Display Name

Solr

Description

The Solr service. Called 'SOLR' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

SOLR_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

solr_servers

Display Name

Solr Server

Description

The Solr Server role. Called 'SOLR_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

SOLR, RACK

SOLR_COLLECTION**Category**

SOLR_COLLECTION

Name For Cross Entity Aggregate Metrics

solr_collections

Display Name

Solr Collection

Description

A Solr collection. Called 'SOLR_COLLECTION' in queries.

Immutable Attribute Names

solrCollectionName, serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

Entity Name Format

serviceName, solrCollectionName

Entity Display Name Format

null

Parent Metric Entity Type Names

SOLR

SOLR_SHARD**Category**

SOLR_SHARD

Name For Cross Entity Aggregate Metrics

solr_shards

Display Name

Solr Shard

Description

A Solr shard. Called 'SOLR_SHARD' in queries.

Immutable Attribute Names

solrCollectionName, solrShardName, serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names**Entity Name Format**

serviceName, solrCollectionName, solrShardName

Entity Display Name Format

null

Parent Metric Entity Type Names

SOLR_COLLECTION

SOLR_REPLICA**Category**

SOLR_REPLICA

Name For Cross Entity Aggregate Metrics

solr_replicas

Display Name

Solr Replica

Description

A Solr replica. Called 'SOLR_REPLICA' in queries.

Immutable Attribute Names

solrShardName, solrReplicaName, solrCollectionName, serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

roleName

Entity Name Format

serviceName, solrCollectionName, solrShardName, solrReplicaName

Entity Display Name Format

null

Parent Metric Entity Type Names

SOLR_SHARD

KS_INDEXER**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

ks_indexers

Display Name

Key-Value Store Indexer

Description

The Key-Value Store Indexer service. Called 'KS_INDEXER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

HBASE_INDEXER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

hbase_indexers

Display Name

Lily HBase Indexer

Description

The Lily HBase Indexer role. Called 'HBASE_INDEXER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KS_INDEXER, RACK

CORE_SETTINGS

Category	SERVICE
Name For Cross Entity Aggregate Metrics	core_settings
Display Name	Core Configuration
Description	The Core Configuration service. Called 'CORE_SETTINGS' in queries.
Immutable Attribute Names	serviceType, serviceName, clusterName, clusterId
Mutable Attribute Names	serviceDisplayName
Entity Name Format	serviceName
Entity Display Name Format	null
Parent Metric Entity Type Names	CLUSTER

ECS

Category	SERVICE
Name For Cross Entity Aggregate Metrics	ecss
Display Name	common.service.type.ecs
Description	The common.service.type.ecs service. Called 'ECS' in queries.
Immutable Attribute Names	serviceType, serviceName, clusterName, clusterId
Mutable Attribute Names	serviceDisplayName
Entity Name Format	serviceName
Entity Display Name Format	null
Parent Metric Entity Type Names	CLUSTER

ECS_SERVER

Category	ROLE
-----------------	------

Name For Cross Entity Aggregate Metrics

ecs_servers

Display Name

Ecs Server

Description

The Ecs Server role. Called 'ECS_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ECS, RACK

ECS_AGENT**Category**

ROLE

Name For Cross Entity Aggregate Metrics

ecs_agents

Display Name

Ecs Agent

Description

The Ecs Agent role. Called 'ECS_AGENT' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ECS, RACK

DOCKER**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

dockers

Display Name

common.service.type.docker

Description

The common.service.type.docker service. Called 'DOCKER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

DOCKER_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

docker_servers

Display Name

Docker Server

Description

The Docker Server role. Called 'DOCKER_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

DOCKER, RACK

ACCUMULO16**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

accumulo16s

Display Name

Accumulo

Description

The Accumulo service. Called 'ACCUMULO16' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

RANGER_RMS**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

ranger_rmss

Display Name

Ranger RMS

Description

The Ranger RMS service. Called 'RANGER_RMS' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

ACCUMULO_C6**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

accumulo_c6s

Display Name

Accumulo

Description

The Accumulo service. Called 'ACCUMULO_C6' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

STREAMS_REPLICATION_MANAGER

Category

SERVICE

Name For Cross Entity Aggregate Metrics

streams_replication_managers

Display Name

Streams Replication Manager

Description

The Streams Replication Manager service. Called 'STREAMS_REPLICATION_MANAGER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

TEZ

Category

SERVICE

Name For Cross Entity Aggregate Metrics

tezs

Display Name

Tez

Description

The Tez service. Called 'TEZ' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format
null

Parent Metric Entity Type Names
CLUSTER

LUNA_KMS

Category
SERVICE

Name For Cross Entity Aggregate Metrics
luna_kmss

Display Name
Navigator HSM KMS backed by SafeNet Luna HSM

Description
The Navigator HSM KMS backed by SafeNet Luna HSM service. Called 'LUNA_KMS' in queries.

Immutable Attribute Names
serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names
serviceDisplayName

Entity Name Format
serviceName

Entity Display Name Format
null

Parent Metric Entity Type Names
CLUSTER

PROFILER_SCHEDULER

Category
SERVICE

Name For Cross Entity Aggregate Metrics
profiler_schedulers

Display Name
Profiler Scheduler

Description
The Profiler Scheduler service. Called 'PROFILER_SCHEDULER' in queries.

Immutable Attribute Names
serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names
serviceDisplayName

Entity Name Format
serviceName

Entity Display Name Format
null

Parent Metric Entity Type Names

CLUSTER

SPARK3_ON_YARN**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

spark3_on_yarns

Display Name

Spark 3

Description

The Spark 3 service. Called 'SPARK3_ON_YARN' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

RANGER_KMS**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

ranger_kmss

Display Name

Ranger KMS

Description

The Ranger KMS service. Called 'RANGER_KMS' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

ATLAS

Category	SERVICE
Name For Cross Entity Aggregate Metrics	atlas
Display Name	Atlas
Description	The Atlas service. Called 'ATLAS' in queries.
Immutable Attribute Names	serviceType, serviceName, clusterName, clusterId
Mutable Attribute Names	serviceDisplayName
Entity Name Format	serviceName
Entity Display Name Format	null
Parent Metric Entity Type Names	CLUSTER

QUEUEMANAGER

Category	SERVICE
Name For Cross Entity Aggregate Metrics	queuemanagers
Display Name	YARN Queue Manager
Description	The YARN Queue Manager service. Called 'QUEUEMANAGER' in queries.
Immutable Attribute Names	serviceType, serviceName, clusterName, clusterId
Mutable Attribute Names	serviceDisplayName
Entity Name Format	serviceName
Entity Display Name Format	null
Parent Metric Entity Type Names	CLUSTER

KUDU

Category	SERVICE
-----------------	---------

Name For Cross Entity Aggregate Metrics

kodus

Display Name

Kudu

Description

The Kudu service. Called 'KUDU' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

CRUISE_CONTROL**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

cruise_controls

Display Name

Cruise Control

Description

The Cruise Control service. Called 'CRUISE_CONTROL' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

SCHEMAREGISTRY**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

schemaregistrys

Display Name

Schema Registry

Description

The Schema Registry service. Called 'SCHEMAREGISTRY' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

OMID**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

omids

Display Name

Omid

Description

The Omid service. Called 'OMID' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

SPARK_ON_YARN**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

spark_on_yarns

Display Name

Spark

Description

The Spark service. Called 'SPARK_ON_YARN' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

LIVY**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

livys

Display Name

Livy

Description

The Livy service. Called 'LIVY' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

THALES_KMS**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

thales_kmss

Display Name

Navigator HSM KMS backed by Thales HSM

Description

The Navigator HSM KMS backed by Thales HSM service. Called 'THALES_KMS' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

PHOENIX**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

phoenixs

Display Name

Phoenix

Description

The Phoenix service. Called 'PHOENIX' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

RANGER_KMS_KTS**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

ranger_kms_ktss

Display Name

Ranger KMS with Key Trustee Server

Description

The Ranger KMS with Key Trustee Server service. Called 'RANGER_KMS_KTS' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

ISILON**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

isilons

Display Name

Isilon

Description

The Isilon service. Called 'ISILON' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

RANGER_RAZ**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

ranger_razs

Display Name

Ranger Raz

Description

The Ranger Raz service. Called 'RANGER_RAZ' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

KNOX**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

knoxs

Display Name

Knox

Description

The Knox service. Called 'KNOX' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

RANGER**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

rangers

Display Name

Ranger

Description

The Ranger service. Called 'RANGER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

KMS**Category**

Category	SERVICE
Name For Cross Entity Aggregate Metrics	kmss
Display Name	Java KeyStore KMS
Description	The Java KeyStore KMS service. Called 'KMS' in queries.
Immutable Attribute Names	serviceType, serviceName, clusterName, clusterId
Mutable Attribute Names	serviceDisplayName
Entity Name Format	serviceName
Entity Display Name Format	null
Parent Metric Entity Type Names	CLUSTER

ZEPPELIN

Category	SERVICE
Name For Cross Entity Aggregate Metrics	zeppelins
Display Name	Zeppelin
Description	The Zeppelin service. Called 'ZEPPELIN' in queries.
Immutable Attribute Names	serviceType, serviceName, clusterName, clusterId
Mutable Attribute Names	serviceDisplayName
Entity Name Format	serviceName
Entity Display Name Format	null
Parent Metric Entity Type Names	CLUSTER

STREAMS_MESSAGING_MANAGER

Category	SERVICE
Name For Cross Entity Aggregate Metrics	streams_messaging_managers

Display Name

Streams Messaging Manager

Description

The Streams Messaging Manager service. Called 'STREAMS_MESSAGING_MANAGER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

KEYTRUSTEE**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

keytrustees

Display Name

Key Trustee KMS

Description

The Key Trustee KMS service. Called 'KEYTRUSTEE' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

DAS**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

dass

Display Name

Data Analytics Studio

Description

The Data Analytics Studio service. Called 'DAS' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

KEYTRUSTEE_SERVER**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

keytrustee_servers

Display Name

Key Trustee Server

Description

The Key Trustee Server service. Called 'KEYTRUSTEE_SERVER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

OZONE**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

ozones

Display Name

Ozone

Description

The Ozone service. Called 'OZONE' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

QUERY_PROCESSOR**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

query_processors

Display Name

Query Processor

Description

The Query Processor service. Called 'QUERY_PROCESSOR' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

KAFKA**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

kafkas

Display Name

Kafka

Description

The Kafka service. Called 'KAFKA' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

LIVY_FOR_SPARK3**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

livy_for_spark3s

Display Name

Livy for Spark 3

Description

The Livy for Spark 3 service. Called 'LIVY_FOR_SPARK3' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

SQL_STREAM_BUILDER**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

sql_stream_builders

Display Name

SQL Stream Builder

Description

The SQL Stream Builder service. Called 'SQL_STREAM_BUILDER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

PROFILER_MANAGER**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

profiler_managers

Display Name

Profiler Manager

Description

The Profiler Manager service. Called 'PROFILER_MANAGER' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

FLINK**Category**

SERVICE

Name For Cross Entity Aggregate Metrics

flinks

Display Name

Flink

Description

The Flink service. Called 'FLINK' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, clusterId

Mutable Attribute Names

serviceDisplayName

Entity Name Format

serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

CLUSTER

SPARK3_ON_YARN-SPARK3_YARN_HISTORY_SERVER

Category	ROLE
Name For Cross Entity Aggregate Metrics	spark3_on_yarn_spark3_yarn_history_servers
Display Name	History Server
Description	The History Server role. Called 'SPARK3_ON_YARN-SPARK3_YARN_HISTORY_SERVER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	SPARK3_ON_YARN, RACK

PHOENIX-PHOENIX_QUERY_SERVER

Category	ROLE
Name For Cross Entity Aggregate Metrics	phoenix_query_servers
Display Name	Query Server
Description	The Query Server role. Called 'PHOENIX-PHOENIX_QUERY_SERVER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	PHOENIX, RACK

QUERY_PROCESSOR-QUERY_PROCESSOR

Category	ROLE
-----------------	------

Name For Cross Entity Aggregate Metrics

query_processor_query_processors

Display Name

Query Processor

Description

The Query Processor role. Called 'QUERY_PROCESSOR-QUERY_PROCESSOR' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

QUERY_PROCESSOR, RACK

RANGER_RAZ-RANGER_RAZ_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

ranger_raz_servers

Display Name

Ranger Raz Server

Description

The Ranger Raz Server role. Called 'RANGER_RAZ-RANGER_RAZ_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

RANGER_RAZ, RACK

KAFKA-KAFKA_BROKER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

kafka_brokers

Display Name

Kafka Broker

Description

The Kafka Broker role. Called 'KAFKA-KAFKA_BROKER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup, kafkaBrokerId

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA, RACK

KAFKA-KAFKA_MIRROR_MAKER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

kafka_mirror_makers

Display Name

Kafka MirrorMaker

Description

The Kafka MirrorMaker role. Called 'KAFKA-KAFKA_MIRROR_MAKER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA, RACK

KAFKA-KAFKA_CONNECT**Category**

ROLE

Name For Cross Entity Aggregate Metrics

kafka_connects

Display Name

Kafka Connect

Description

The Kafka Connect role. Called 'KAFKA-KAFKA_CONNECT' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA, RACK

CRUISE_CONTROL-CRUISE_CONTROL_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

cruise_control_servers

Display Name

Cruise Control Server

Description

The Cruise Control Server role. Called 'CRUISE_CONTROL-CRUISE_CONTROL_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

CRUISE_CONTROL, RACK

STREAMS_MESSAGING_MANAGER-STREAMS_MESSAGING_MANAGER_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

streams_messaging_manager_servers

Display Name

Streams Messaging Manager Rest Admin Server

Description

The Streams Messaging Manager Rest Admin Server role. Called 'STREAMS_MESSAGING_MANAGER-STREAMS_MESSAGING_MANAGER_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

STREAMS_MESSAGING_MANAGER, RACK

STREAMS_MESSAGING_MANAGER-STREAMS_MESSAGING_MANAGER_UI**Category**

ROLE

Name For Cross Entity Aggregate Metrics

streams_messaging_manager_uis

Display Name

Streams Messaging Manager UI Server

Description

The Streams Messaging Manager UI Server role. Called 'STREAMS_MESSAGING_MANAGER-STREAMS_MESSAGING_MANAGER_UI' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

STREAMS_MESSAGING_MANAGER, RACK

LIVY-LIVY_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

livy_servers

Display Name

Livy Server

Description

The Livy Server role. Called 'LIVY-LIVY_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

LIVY, RACK

OZONE-STORAGE_CONTAINER_MANAGER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

ozone_scms

Display Name

Storage Container Manager

Description

The Storage Container Manager role. Called 'OZONE-STORAGE_CONTAINER_MANAGER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

OZONE, RACK

OZONE-OZONE_MANAGER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

ozone_managers

Display Name

Ozone Manager

Description

The Ozone Manager role. Called 'OZONE-OZONE_MANAGER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
OZONE, RACK

OZONE-OZONE_RECON

Category
ROLE

Name For Cross Entity Aggregate Metrics
ozone_recons

Display Name
Ozone Recon

Description
The Ozone Recon role. Called 'OZONE-OZONE_RECON' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
OZONE, RACK

OZONE-OZONE_DATANODE

Category
ROLE

Name For Cross Entity Aggregate Metrics
ozone_datanodes

Display Name
Ozone DataNode

Description
The Ozone DataNode role. Called 'OZONE-OZONE_DATANODE' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names

OZONE, RACK

OZONE-S3_GATEWAY**Category**

ROLE

Name For Cross Entity Aggregate Metrics

ozone_s3_gateways

Display Name

S3 Gateway

Description

The S3 Gateway role. Called 'OZONE-S3_GATEWAY' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

OZONE, RACK

OZONE-OZONE_PROMETHEUS**Category**

ROLE

Name For Cross Entity Aggregate Metrics

ozone_prometheuss

Display Name

Ozone Prometheus

Description

The Ozone Prometheus role. Called 'OZONE-OZONE_PROMETHEUS' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

OZONE, RACK

RANGER_RMS-RANGER_RMS_SERVER

Category	ROLE
Name For Cross Entity Aggregate Metrics	ranger_rms_servers
Display Name	Ranger RMS Server
Description	The Ranger RMS Server role. Called 'RANGER_RMS-RANGER_RMS_SERVER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	RANGER_RMS, RACK

RANGER-RANGER_ADMIN

Category	ROLE
Name For Cross Entity Aggregate Metrics	ranger_admins
Display Name	Ranger Admin
Description	The Ranger Admin role. Called 'RANGER-RANGER_ADMIN' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	RANGER, RACK

RANGER-RANGER_USERSYNC

Category	ROLE
-----------------	------

Name For Cross Entity Aggregate Metrics

ranger_usersyncs

Display Name

Ranger Usersync

Description

The Ranger Usersync role. Called 'RANGER-RANGER_USERSYNC' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

RANGER, RACK

RANGER-RANGER_TAGSYNC**Category**

ROLE

Name For Cross Entity Aggregate Metrics

ranger_tagsyncs

Display Name

Ranger Tagsync

Description

The Ranger Tagsync role. Called 'RANGER-RANGER_TAGSYNC' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

RANGER, RACK

OMID-OMID_TSO**Category**

ROLE

Name For Cross Entity Aggregate Metrics

omid_tsos

Display Name

Omid tso server

Description

The Omid tso server role. Called 'OMID-OMID_TSO' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

OMID, RACK

KUDU-KUDU_MASTER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

kudu_masters

Display Name

Master

Description

The Master role. Called 'KUDU-KUDU_MASTER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KUDU, RACK

KUDU-KUDU_TSERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

kudu_tservers

Display Name

Tablet Server

Description

The Tablet Server role. Called 'KUDU-KUDU_TSERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KUDU, RACK

STREAMS_REPLICATION_MANAGER-STREAMS_REPLICATION_MANAGER_DRIVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

streams_replication_manager_drivers

Display Name

SRM Driver

Description

The SRM Driver role. Called 'STREAMS_REPLICATION_MANAGER-STREAMS_REPLICATION_MANAGER_DRIVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

STREAMS_REPLICATION_MANAGER, RACK

STREAMS_REPLICATION_MANAGER-STREAMS_REPLICATION_MANAGER_SERVICE**Category**

ROLE

Name For Cross Entity Aggregate Metrics

streams_replication_manager_services

Display Name

SRM Service

Description

The SRM Service role. Called 'STREAMS_REPLICATION_MANAGER-STREAMS_REPLICATION_MANAGER_SERVICE' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

STREAMS_REPLICATION_MANAGER, RACK

KNOX-KNOX_GATEWAY**Category**

ROLE

Name For Cross Entity Aggregate Metrics

knox_gateways

Display Name

Knox Gateway

Description

The Knox Gateway role. Called 'KNOX-KNOX_GATEWAY' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KNOX, RACK

KNOX-IDBROKER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

knox_idbrokers

Display Name

Knox IDBroker

Description

The Knox IDBroker role. Called 'KNOX-IDBROKER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
KNOX, RACK

QUEUEMANAGER-QUEUEMANAGER_WEBAPP

Category
ROLE

Name For Cross Entity Aggregate Metrics
queuemanager_webapps

Display Name
YARN Queue Manager Webapp

Description
The YARN Queue Manager Webapp role. Called 'QUEUEMANAGER-QUEUEMANAGER_WEBAPP' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
QUEUEMANAGER, RACK

QUEUEMANAGER-QUEUEMANAGER_STORE

Category
ROLE

Name For Cross Entity Aggregate Metrics
queuemanager_stores

Display Name
YARN Queue Manager Store

Description
The YARN Queue Manager Store role. Called 'QUEUEMANAGER-QUEUEMANAGER_STORE' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

QUEUEMANAGER, RACK

ATLAS-ATLAS_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

atlas_servers

Display Name

Atlas Server

Description

The Atlas Server role. Called 'ATLAS-ATLAS_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ATLAS, RACK

SPARK_ON_YARN-SPARK_YARN_HISTORY_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

spark_on_yarn_spark_yarn_history_servers

Display Name

History Server

Description

The History Server role. Called 'SPARK_ON_YARN-SPARK_YARN_HISTORY_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

SPARK_ON_YARN, RACK

SCHEMAREGISTRY-SCHEMA_REGISTRY_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

schemaregistry_schema_registry_servers

Display Name

Schema Registry Server

Description

The Schema Registry Server role. Called 'SCHEMAREGISTRY-SCHEMA_REGISTRY_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

SCHEMAREGISTRY, RACK

LIVY_FOR_SPARK3-LIVY_SERVER_FOR_SPARK3**Category**

ROLE

Name For Cross Entity Aggregate Metrics

livy_for_spark3_livy_server_for_spark3s

Display Name

Livy Server for Spark 3

Description

The Livy Server for Spark 3 role. Called 'LIVY_FOR_SPARK3-LIVY_SERVER_FOR_SPARK3' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

LIVY_FOR_SPARK3, RACK

RANGER_KMS_KTS-RANGER_KMS_SERVER_KTS

Category	ROLE
Name For Cross Entity Aggregate Metrics	ranger_kms_kts_ranger_kms_server_ktss
Display Name	Ranger KMS Server with KTS
Description	The Ranger KMS Server with KTS role. Called 'RANGER_KMS_KTS-RANGER_KMS_SERVER_KTS' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	RANGER_KMS_KTS, RACK

ZEPPELIN-ZEPPELIN_SERVER

Category	ROLE
Name For Cross Entity Aggregate Metrics	zeppelin_servers
Display Name	Zeppelin Server
Description	The Zeppelin Server role. Called 'ZEPPELIN-ZEPPELIN_SERVER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	ZEPPELIN, RACK

LUNA_KMS-HSMKP_LUNA

Category	ROLE
-----------------	------

Name For Cross Entity Aggregate Metrics

luna_kms_hsmkp_lunas

Display Name

Navigator Luna KMS Proxy

Description

The Navigator Luna KMS Proxy role. Called 'LUNA_KMS-HSMKP_LUNA' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

LUNA_KMS, RACK

LUNA_KMS-HSMKP_METASTORE_LUNA**Category**

ROLE

Name For Cross Entity Aggregate Metrics

luna_kms_hsmkp_metastore_lunas

Display Name

Navigator Luna KMS Metastore

Description

The Navigator Luna KMS Metastore role. Called 'LUNA_KMS-HSMKP_METASTORE_LUNA' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

LUNA_KMS, RACK

RANGER_KMS-RANGER_KMS_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

ranger_kms_servers

Display Name

Ranger KMS Server

Description

The Ranger KMS Server role. Called 'RANGER_KMS-RANGER_KMS_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

RANGER_KMS, RACK

DAS-DAS_WEBAPP**Category**

ROLE

Name For Cross Entity Aggregate Metrics

das_webapps

Display Name

Data Analytics Studio Webapp Server

Description

The Data Analytics Studio Webapp Server role. Called 'DAS-DAS_WEBAPP' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

DAS, RACK

DAS-DAS_EVENT_PROCESSOR**Category**

ROLE

Name For Cross Entity Aggregate Metrics

das_event_processors

Display Name

Data Analytics Studio Eventprocessor

Description

The Data Analytics Studio Eventprocessor role. Called 'DAS-DAS_EVENT_PROCESSOR' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

DAS, RACK

KMS-KMS**Category**

ROLE

Name For Cross Entity Aggregate Metrics

kms_servers

Display Name

Key Management Server

Description

The Key Management Server role. Called 'KMS-KMS' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KMS, RACK

PROFILER_SCHEDULER-PROFILER_SCHEDULER_AGENT**Category**

ROLE

Name For Cross Entity Aggregate Metrics

profiler_scheduler_agents

Display Name

Profiler Scheduler Agent

Description

The Profiler Scheduler Agent role. Called 'PROFILER_SCHEDULER-PROFILER_SCHEDULER_AGENT' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

PROFILER_SCHEDULER, RACK

ACCUMULO16-ACCUMULO16_MASTER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

accumulo16_masters

Display Name

Master

Description

The Master role. Called 'ACCUMULO16-ACCUMULO16_MASTER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ACCUMULO16, RACK

ACCUMULO16-ACCUMULO16_TSERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

accumulo16_tservers

Display Name

Tablet Server

Description

The Tablet Server role. Called 'ACCUMULO16-ACCUMULO16_TSERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ACCUMULO16, RACK

ACCUMULO16-ACCUMULO16_GC**Category**

ROLE

Name For Cross Entity Aggregate Metrics

accumulo16_gcs

Display Name

Garbage Collector

Description

The Garbage Collector role. Called 'ACCUMULO16-ACCUMULO16_GC' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ACCUMULO16, RACK

ACCUMULO16-ACCUMULO16_MONITOR**Category**

ROLE

Name For Cross Entity Aggregate Metrics

accumulo16_monitors

Display Name

Monitor

Description

The Monitor role. Called 'ACCUMULO16-ACCUMULO16_MONITOR' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ACCUMULO16, RACK

ACCUMULO16-ACCUMULO16_TRACER

Category

ROLE

Name For Cross Entity Aggregate Metrics

accumulo16_tracers

Display Name

Tracer

Description

The Tracer role. Called 'ACCUMULO16-ACCUMULO16_TRACER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ACCUMULO16, RACK

PROFILER_MANAGER-PROFILER_ADMIN_AGENT

Category

ROLE

Name For Cross Entity Aggregate Metrics

profiler_manager_profiler_admin_agents

Display Name

Profiler Admin Agent

Description

The Profiler Admin Agent role. Called 'PROFILER_MANAGER-PROFILER_ADMIN_AGENT' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

PROFILER_MANAGER, RACK

PROFILER_MANAGER-DATA_DISCOVERY_SERVICE_AGENT

Category

ROLE

Name For Cross Entity Aggregate Metrics

profiler_manager_data_discovery_service_agents

Display Name

Data Discovery Service Agent

Description

The Data Discovery Service Agent role. Called 'PROFILER_MANAGER-DATA_DISCOVERY_SERVICE_AGENT' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

PROFILER_MANAGER, RACK

PROFILER_MANAGER-PROFILER_METRICS_AGENT

Category

ROLE

Name For Cross Entity Aggregate Metrics

profiler_manager_profiler_metrics_agents

Display Name

Profiler Metrics Agent

Description

The Profiler Metrics Agent role. Called 'PROFILER_MANAGER-PROFILER_METRICS_AGENT' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

PROFILER_MANAGER, RACK

KEYTRUSTEE_SERVER-KEYTRUSTEE_ACTIVE_SERVER

Category	ROLE
Name For Cross Entity Aggregate Metrics	keytrustee_server_keytrustee_active_servers
Display Name	Active Key Trustee Server
Description	The Active Key Trustee Server role. Called 'KEYTRUSTEE_SERVER-KEYTRUSTEE_ACTIVE_SERVER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	KEYTRUSTEE_SERVER, RACK

KEYTRUSTEE_SERVER-KEYTRUSTEE_PASSIVE_SERVER

Category	ROLE
Name For Cross Entity Aggregate Metrics	keytrustee_server_keytrustee_passive_servers
Display Name	Passive Key Trustee Server
Description	The Passive Key Trustee Server role. Called 'KEYTRUSTEE_SERVER-KEYTRUSTEE_PASSIVE_SERVER' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	KEYTRUSTEE_SERVER, RACK

KEYTRUSTEE_SERVER-DB_ACTIVE

Category

Category	ROLE
Name For Cross Entity Aggregate Metrics	keytrustee_server_db_actives
Display Name	Active Database
Description	The Active Database role. Called 'KEYTRUSTEE_SERVER-DB_ACTIVE' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	KEYTRUSTEE_SERVER, RACK

KEYTRUSTEE_SERVER-DB_PASSIVE

Category	ROLE
Name For Cross Entity Aggregate Metrics	keytrustee_server_db_passives
Display Name	Passive Database
Description	The Passive Database role. Called 'KEYTRUSTEE_SERVER-DB_PASSIVE' in queries.
Immutable Attribute Names	serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId
Mutable Attribute Names	roleConfigGroup
Entity Name Format	roleName
Entity Display Name Format	null
Parent Metric Entity Type Names	KEYTRUSTEE_SERVER, RACK

THALES_KMS-HSMKP_THALES

Category	ROLE
Name For Cross Entity Aggregate Metrics	thales_kms_hsmkp_thales

Display Name

Navigator Thales KMS Proxy

Description

The Navigator Thales KMS Proxy role. Called 'THALES_KMS-HSMKP_THALES' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

THALES_KMS, RACK

THALES_KMS-HSMKP_METASTORE_THALES**Category**

ROLE

Name For Cross Entity Aggregate Metrics

thales_kms_hsmkp_metastore_thales

Display Name

Navigator Thales KMS Metastore

Description

The Navigator Thales KMS Metastore role. Called 'THALES_KMS-HSMKP_METASTORE_THALES' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

THALES_KMS, RACK

FLINK-FLINK_HISTORY_SERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

flink_history_servers

Display Name

Flink Dashboard

Description

The Flink Dashboard role. Called 'FLINK-FLINK_HISTORY_SERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

FLINK, RACK

KEYTRUSTEE-KMS_KEYTRUSTEE**Category**

ROLE

Name For Cross Entity Aggregate Metrics

keytrustee_kms_keytrustees

Display Name

Key Management Server Proxy

Description

The Key Management Server Proxy role. Called 'KEYTRUSTEE-KMS_KEYTRUSTEE' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

KEYTRUSTEE, RACK

ACCUMULO_C6-ACCUMULO_MASTER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

accumulo_c6_accumulo_masters

Display Name

Master

Description

The Master role. Called 'ACCUMULO_C6-ACCUMULO_MASTER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ACCUMULO_C6, RACK

ACCUMULO_C6-ACCUMULO_TSERVER**Category**

ROLE

Name For Cross Entity Aggregate Metrics

accumulo_c6_accumulo_tservers

Display Name

Tablet Server

Description

The Tablet Server role. Called 'ACCUMULO_C6-ACCUMULO_TSERVER' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ACCUMULO_C6, RACK

ACCUMULO_C6-ACCUMULO_GC**Category**

ROLE

Name For Cross Entity Aggregate Metrics

accumulo_c6_accumulo_gcs

Display Name

Garbage Collector

Description

The Garbage Collector role. Called 'ACCUMULO_C6-ACCUMULO_GC' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
ACCUMULO_C6, RACK

ACCUMULO_C6-ACCUMULO_MONITOR

Category
ROLE

Name For Cross Entity Aggregate Metrics
accumulo_c6_accumulo_monitors

Display Name
Monitor

Description
The Monitor role. Called 'ACCUMULO_C6-ACCUMULO_MONITOR' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format
null

Parent Metric Entity Type Names
ACCUMULO_C6, RACK

ACCUMULO_C6-ACCUMULO_TRACER

Category
ROLE

Name For Cross Entity Aggregate Metrics
accumulo_c6_accumulo_tracers

Display Name
Tracer

Description
The Tracer role. Called 'ACCUMULO_C6-ACCUMULO_TRACER' in queries.

Immutable Attribute Names
serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names
roleConfigGroup

Entity Name Format
roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

ACCUMULO_C6, RACK

SQL_STREAM_BUILDER-STREAMING_SQL_ENGINE**Category**

ROLE

Name For Cross Entity Aggregate Metrics

sql_stream_builder_streaming_sql_engines

Display Name

Streaming SQL Engine

Description

The Streaming SQL Engine role. Called 'SQL_STREAM_BUILDER-STREAMING_SQL_ENGINE' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

SQL_STREAM_BUILDER, RACK

SQL_STREAM_BUILDER-MATERIALIZED_VIEW_ENGINE**Category**

ROLE

Name For Cross Entity Aggregate Metrics

sql_stream_builder_materialized_view_engines

Display Name

Materialized View Engine

Description

The Materialized View Engine role. Called 'SQL_STREAM_BUILDER-MATERIALIZED_VIEW_ENGINE' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

SQL_STREAM_BUILDER, RACK

SQL_STREAM_BUILDER-STREAMING_SQL_CONSOLE**Category**

ROLE

Name For Cross Entity Aggregate Metrics

sql_stream_builder_streaming_sql_consoles

Display Name

Streaming SQL Console

Description

The Streaming SQL Console role. Called 'SQL_STREAM_BUILDER-STREAMING_SQL_CONSOLE' in queries.

Immutable Attribute Names

serviceType, roleType, hostname, serviceName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names

roleConfigGroup

Entity Name Format

roleName

Entity Display Name Format

null

Parent Metric Entity Type Names

SQL_STREAM_BUILDER, RACK

KAFKA_BROKER_LOG_DIRECTORY**Category**

KAFKA_BROKER_LOG_DIRECTORY

Name For Cross Entity Aggregate Metrics

kafka_broker_log_directories

Display Name

Kafka Broker Log Directory

Description

A Kafka Broker Log Directory. Called 'KAFKA_BROKER_LOG_DIRECTORY' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, hostname, clusterName, hostId, roleName, clusterId, rackId,
kafkaLogDirectoryPath

Mutable Attribute Names**Entity Name Format**

roleName, kafkaLogDirectoryPath

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA-KAFKA_BROKER

KAFKA_TOPIC

Category	KAFKA_TOPIC
Name For Cross Entity Aggregate Metrics	kafka_topics
Display Name	Kafka Topic
Description	A Kafka topic. Called 'KAFKA_TOPIC' in queries.
Immutable Attribute Names	kafkaTopicName, serviceName, kafkaInternalTopic
Mutable Attribute Names	
Entity Name Format	serviceName, kafkaTopicName
Entity Display Name Format	null
Parent Metric Entity Type Names	

KAFKA_BROKER_TOPIC

Category	KAFKA_BROKER_TOPIC
Name For Cross Entity Aggregate Metrics	kafka_broker_topics
Display Name	Kafka Broker Topic
Description	Broker view of a specific topic. Called 'KAFKA_BROKER_TOPIC' in queries.
Immutable Attribute Names	serviceType, kafkaTopicName, serviceName, roleType, hostname, clusterName, hostId, roleName, clusterId, rackId, kafkaInternalTopic
Mutable Attribute Names	
Entity Name Format	roleName, kafkaTopicName
Entity Display Name Format	null
Parent Metric Entity Type Names	KAFKA-KAFKA_BROKER, KAFKA_TOPIC

KAFKA_REPLICA

Category	KAFKA_REPLICA
Name For Cross Entity Aggregate Metrics	kafka_replicas

Display Name

Kafka Replica

Description

A replica for a given partition of a Kafka topic. Called 'KAFKA_REPLICA' in queries.

Immutable Attribute Names

serviceType, kafkaTopicName, serviceName, roleType, hostname, clusterName, kafkaPartitionId, hostId, roleName, clusterId, rackId, kafkaInternalTopic

Mutable Attribute Names**Entity Name Format**

roleName, kafkaTopicName, kafkaPartitionId

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA-KAFKA_BROKER, KAFKA_BROKER_TOPIC

KAFKA_BROKER_TOPIC_PARTITION**Category**

KAFKA_BROKER_TOPIC_PARTITION

Name For Cross Entity Aggregate Metrics

kafka_broker_topic_partitions

Display Name

Kafka Broker Topic Partition

Description

Broker view of a specific topic partition. Called 'KAFKA_BROKER_TOPIC_PARTITION' in queries.

Immutable Attribute Names

serviceType, kafkaTopicName, serviceName, roleType, hostname, clusterName, kafkaPartitionId, hostId, roleName, clusterId, rackId, kafkaInternalTopic

Mutable Attribute Names**Entity Name Format**

roleName, kafkaTopicName, kafkaPartitionId

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA-KAFKA_BROKER, KAFKA_BROKER_TOPIC

KAFKA_PRODUCER**Category**

KAFKA_PRODUCER

Name For Cross Entity Aggregate Metrics

kafka_producers

Display Name

Kafka Producer

Description

Kafka producers. Called 'KAFKA_PRODUCER' in queries.

Immutable Attribute Names

serviceType, kafkaPartitionId, hostId, clusterId, serviceName, kafkaTopicName, roleType, hostname, clusterName, roleName, kafkaClientId, rackId, kafkaInternalTopic

Mutable Attribute Names**Entity Name Format**

roleName, kafkaClientId, kafkaTopicName, kafkaPartitionId

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA_BROKER_TOPIC_PARTITION, KAFKA-KAFKA_BROKER

KAFKA_CONSUMER_GROUP**Category**

KAFKA_CONSUMER_GROUP

Name For Cross Entity Aggregate Metrics

kafka_consumer_groups

Display Name

Kafka Consumer Group

Description

Kafka consumer group metrics. Called 'KAFKA_CONSUMER_GROUP' in queries.

Immutable Attribute Names

serviceName, kafkaConsumerGroup

Mutable Attribute Names**Entity Name Format**

serviceName, kafkaConsumerGroup

Entity Display Name Format

null

Parent Metric Entity Type Names**KAFKA_CONNECT_CONNECTOR_TASK_METRICS****Category**

KAFKA_CONNECT_CONNECTOR_TASK_METRICS

Name For Cross Entity Aggregate Metrics

kafka_connect_connector_task_metrics

Display Name

Kafka Connect Connector Task Metrics

Description

Kafka Connect Connector task metrics. Called 'KAFKA_CONNECT_CONNECTOR_TASK_METRICS' in queries.

Immutable Attribute Names

kafkaConnectConnectorName, serviceType, serviceName, roleType, hostname,
kafkaConnectConnectorTaskId, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names**Entity Name Format**

roleName, kafkaConnectConnectorName, kafkaConnectConnectorTaskId

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA-KAFKA_CONNECT

KAFKA_CONNECT_CONNECTOR_SINK_TASK_METRICS**Category**

KAFKA_CONNECT_CONNECTOR_SINK_TASK_METRICS

Name For Cross Entity Aggregate Metrics

kafka_connect_connector_sink_task_metrics

Display Name

Kafka Connect Connector Sink Task Metrics

Description

Kafka Connect Connector sink task metrics. Called
'KAFKA_CONNECT_CONNECTOR_SINK_TASK_METRICS' in queries.

Immutable Attribute Names

kafkaConnectConnectorName, serviceType, serviceName, roleType, hostname,
kafkaConnectConnectorTaskId, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names**Entity Name Format**

roleName, kafkaConnectConnectorName, kafkaConnectConnectorTaskId

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA-KAFKA_CONNECT

KAFKA_CONNECT_CONNECTOR_SOURCE_TASK_METRICS**Category**

KAFKA_CONNECT_CONNECTOR_SOURCE_TASK_METRICS

Name For Cross Entity Aggregate Metrics

kafka_connect_connector_source_task_metrics

Display Name

Kafka Connect Connector Source Task Metrics

Description

Kafka Connect Connector source task metrics. Called
'KAFKA_CONNECT_CONNECTOR_SOURCE_TASK_METRICS' in queries.

Immutable Attribute Names

kafkaConnectConnectorName, serviceType, serviceName, roleType, hostname,
kafkaConnectConnectorTaskId, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names**Entity Name Format**

roleName, kafkaConnectConnectorName, kafkaConnectConnectorTaskId

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA-KAFKA_CONNECT

KAFKA_CONNECT_CONNECTOR_TASK_ERROR_METRICS**Category**

KAFKA_CONNECT_CONNECTOR_TASK_ERROR_METRICS

Name For Cross Entity Aggregate Metrics

kafka_connect_connector_task_error_metrics

Display Name

Kafka Connect Connector Task Error Metrics

Description

Kafka Connect Connector task error metrics. Called 'KAFKA_CONNECT_CONNECTOR_TASK_ERROR_METRICS' in queries.

Immutable Attribute Names

kafkaConnectConnectorName, serviceType, serviceName, roleType, hostname, kafkaConnectConnectorTaskId, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names**Entity Name Format**

roleName, kafkaConnectConnectorName, kafkaConnectConnectorTaskId

Entity Display Name Format

null

Parent Metric Entity Type Names

KAFKA-KAFKA_CONNECT

KUDU_TABLE**Category**

KUDU_TABLE

Name For Cross Entity Aggregate Metrics

kudu_tables

Display Name

Kudu Table

Description

A Kudu table. Called 'KUDU_TABLE' in queries.

Immutable Attribute Names

serviceType, serviceName, clusterName, kuduTableId, clusterId

Mutable Attribute Names

kuduTableState, kuduTableName

Entity Name Format

serviceName, kuduTableId

Entity Display Name Format

null

Parent Metric Entity Type Names

KUDU

KUDU_TABLET**Category**

KUDU_TABLET

Name For Cross Entity Aggregate Metrics

kudu_tablets

Display Name

Kudu Tablet

Description

A Kudu tablet. Called 'KUDU_TABLET' in queries.

Immutable Attribute Names

serviceType, serviceName, kuduTableId, clusterName, kuduTableId, clusterId

Mutable Attribute Names

kuduTabletState

Entity Name Format

serviceName, kuduTableId

Entity Display Name Format

null

Parent Metric Entity Type Names

KUDU_TABLE

KUDU_REPLICA**Category**

KUDU_REPLICA

Name For Cross Entity Aggregate Metrics

kudu_replicas

Display Name

Kudu Replica

Description

A Kudu replica. Called 'KUDU_REPLICA' in queries.

Immutable Attribute Names

serviceType, kuduTableId, serviceName, roleType, hostname, clusterName, kuduTableId, hostId, roleName, clusterId, rackId

Mutable Attribute Names**Entity Name Format**

roleName, kuduTableId

Entity Display Name Format

null

Parent Metric Entity Type Names

KUDU_TABLET, KUDU-KUDU_TSERVER

STREAMS_REPLICATION_MANAGER_HERDER**Category**

STREAMS_REPLICATION_MANAGER_HERDER

Name For Cross Entity Aggregate Metrics

streams_replication_manager_herders

Display Name

SRM Distributed Herder metrics

Description

SRM Distributed Herder metrics. Called 'STREAMS_REPLICATION_MANAGER_HERDER' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, hostname, streams_replication_manager_herder_name, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names**Entity Name Format**

roleName, streams_replication_manager_herder_name

Entity Display Name Format

null

Parent Metric Entity Type Names

STREAMS_REPLICATION_MANAGER-STREAMS_REPLICATION_MANAGER_DRIVER

IMPALA_DAEMON_POOL**Category**

IMPALA_DAEMON_POOL

Name For Cross Entity Aggregate Metrics

impala_daemon_pools

Display Name

Impala Daemon Resource Pool

Description

An Impala Daemon's view of a resource pool. Called 'IMPALA_DAEMON_POOL' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, hostname, clusterName, hostId, roleName, clusterId, rackId, poolName

Mutable Attribute Names**Entity Name Format**

roleName, poolName

Entity Display Name Format

null

Parent Metric Entity Type Names

IMPALA_POOL, IMPALAD

HIVE_ON_TEZ_TABLE

Category

HIVE_ON_TEZ_TABLE

Name For Cross Entity Aggregate Metrics

hive_on_tez_tables

Display Name

Hive Table

Description

Hive Table level metrics Called 'HIVE_ON_TEZ_TABLE' in queries.

Immutable Attribute Names

serviceType, serviceName, roleType, hostname, hive_on_tezTableName, clusterName, hostId, roleName, clusterId, rackId

Mutable Attribute Names**Entity Name Format**

hive_on_tezTableName, roleName, serviceName

Entity Display Name Format

null

Parent Metric Entity Type Names

HIVE_ON_TEZ_HIVESERVER2

Cloudera Manager Entity Type Attributes

Reference information about Entity Type attributes used by Cloudera Manager

entityName

Display Name

Entity Name

Description

The name of this entity. Entity names are immutable and are unique within a given entity category. Called 'entityName' in queries.

Value Case Sensitive?

false

category

Display Name

Category

Description

The category of this entity. Called 'category' in queries.

Value Case Sensitive?

false

version

Display Name

Version

Description

The software version associated with this entity. Called 'version' in queries.

Value Case Sensitive?

false

active**Display Name**

Active

Description

Whether or not this entity is considered active. Entities are considered inactive when Cloudera Manager believes they have been deleted. Inactive entities are hidden by default in queries. Called 'active' in queries.

Value Case Sensitive?

false

roleName**Display Name**

Role Name

Description

The name of the role associated with this entity. This is the immutable identifier of a role in Cloudera Manager. Called 'roleName' in queries.

Value Case Sensitive?

false

roleType**Display Name**

Role Type

Description

The type of the role associated with this entity. Called 'roleType' in queries.

Value Case Sensitive?

false

roleState**Display Name**

Role State

Description

The runtime state of the role associated with this entity. Called 'roleState' in queries.

Value Case Sensitive?

false

roleConfigGroup**Display Name**

Role Config Group

Description

The name of the role config group associated with this entity. This is the immutable identifier of a role config group in Cloudera Manager. Called 'roleConfigGroup' in queries.

Value Case Sensitive?

true

serviceName**Display Name**

Service Name

Description

The name of the service associated with this entity. This is the immutable identifier of a service in Cloudera Manager. Called 'serviceName' in queries.

Value Case Sensitive?

false

serviceDisplayName**Display Name**

Service Display Name

Description

The display name of the service associated with this entity. Called 'serviceDisplayName' in queries.

Value Case Sensitive?

true

serviceType**Display Name**

Service Type

Description

The type of the service associated with this entity. Called 'serviceType' in queries.

Value Case Sensitive?

false

serviceState**Display Name**

Service State

Description

The runtime state of the service associated with this entity. Called 'serviceState' in queries.

Value Case Sensitive?

false

userName**Display Name**

Username

Description

The user name associated with this entity. Called 'userName' in queries.

Value Case Sensitive?

true

groupName**Display Name**

Group Name

Description

The name of the group associated with this entity. Called 'groupName' in queries.

Value Case Sensitive?

true

ownerName**Display Name**

Owner Name

Description

The name of the owner associated with this entity. Called 'ownerName' in queries.

Value Case Sensitive?

true

queueName**Display Name**

Queue Name

Description

The name of the queue associated with this entity. This attribute is interchangeable with the 'poolName' attribute. Called 'queueName' in queries.

Value Case Sensitive?

true

poolName**Display Name**

Pool Name

Description

The name of the pool associated with this entity. This attribute is interchangeable with the 'queueName' attribute. Called 'poolName' in queries.

Value Case Sensitive?

true

path**Display Name**

Path

Description

The name of the path associated with this entity. Called 'path' in queries.

Value Case Sensitive?

true

expired**Display Name**

Expired

Description

Whether or not this entity is considered expired. Called 'expired' in queries.

Value Case Sensitive?

false

clusterId**Display Name**

Cluster ID

Description

The ID of the cluster associated with this entity. This attribute is deprecated. The 'clusterName' attribute should be used instead. Called 'clusterId' in queries.

Value Case Sensitive?

false

clusterName**Display Name**

Cluster Name

Description

The name of the cluster associated with this entity. This is the immutable identifier of a cluster in Cloudera Manager. Called 'clusterName' in queries.

Value Case Sensitive?

false

clusterDisplayName**Display Name**

Cluster Display Name

Description

The display name of the cluster associated with this entity. Called 'clusterDisplayName' in queries.

Value Case Sensitive?

true

rackId**Display Name**

Rack ID

Description

The ID of the rack associated with this entity. Called 'rackId' in queries.

Value Case Sensitive?

true

hostId**Display Name**

Host ID

Description

The ID of the host associated with this entity. This is the immutable identifier of a host in Cloudera Manager. Called 'hostId' in queries.

Value Case Sensitive?

false

hostname

Display Name

Hostname

Description

The hostname of the host associated with this entity. Called 'hostname' in queries.

Value Case Sensitive?

true

interface

Display Name

Interface

Description

The interface name of the network interface associated with this entity. Called 'interface' in queries.

Value Case Sensitive?

false

device

Display Name

Device

Description

The device name of the disk associated with this entity. Called 'device' in queries.

Value Case Sensitive?

false

logicalPartition

Display Name

Logical Partition

Description

Whether or not the disk device associated with this entity is a logical partition. Called 'logicalPartition' in queries.

Value Case Sensitive?

false

partition

Display Name

Partition

Description

The name of the partition associated with this entity. Called 'partition' in queries.

Value Case Sensitive?

false

mountpoint

Display Name

Mountpoint

Description

The mountpoint of the filesystem associated with this entity. Called 'mountpoint' in queries.

Value Case Sensitive?

true

mountOptions

Display Name

Mount Options

Description

The mount options of the filesystem associated with this entity. Called 'mountOptions' in queries.

Value Case Sensitive?

true

filesystemType

Display Name

Filesystem Type

Description

The type of filesystem (e.g. nfs, xfs, ext3). Called 'filesystemType' in queries.

Value Case Sensitive?

false

nameserviceName

Display Name

Nameservice Name

Description

The name of the HDFS nameservice associated with this entity. Called 'nameserviceName' in queries.

Value Case Sensitive?

true

cached

Display Name

Cache ID

Description

The ID of the cache directive associated with this entity. Called 'cacheId' in queries.

Value Case Sensitive?

false

hnamespaceName

Display Name

HNamespace Name

Description

The name of the HBase namespace associated with this entity. Called 'hnamespaceName' in queries.

Value Case Sensitive?

true

htableName

Display Name

HTable Name

Description

The name of the HBase table associated with this entity. Called 'htableName' in queries.

Value Case Sensitive?

true

systemTable

Display Name

System Table

Description

Whether or not the table associated with this entity is a system table. Called 'systemTable' in queries.

Value Case Sensitive?

false

hregionName

Display Name

HRegion Name

Description

The name of the HBase region associated with this entity. Called 'hregionName' in queries.

Value Case Sensitive?

false

hbaseReplicationPeerId

Display Name

HBase Replication Peer ID

Description

The ID of the HBase replication peer associated with this entity. Called 'hbaseReplicationPeerId' in queries.

Value Case Sensitive?

true

hbaseReplicationPeerClusterKey

Display Name

HBase Replication Peer Cluster Key

Description

The cluster key of the HBase replication peer associated with this entity. The cluster key contains a list of ZooKeeper nodes in the cluster's quorum, the client port for the ZooKeeper quorum, and the base znode for HBase in HDFS on that cluster. Called 'hbaseReplicationPeerClusterKey' in queries.

Value Case Sensitive?

true

timeSeriesTableName

Display Name

Time-Series Table Name

Description

The name of the time-series table associated with this entity. Called 'timeSeriesTableName' in queries.

Value Case Sensitive?

false

timeSeriesApplicationName

Display Name

Time-Series Application Name

Description

The name of the time-series application associated with this entity. Called 'timeSeriesApplicationName' in queries.

Value Case Sensitive?

false

rollup

Display Name

Rollup

Description

The granularity of the data in the time-series table associated with this entity. Values include "RAW", "TEN_MINUTELY", "HOURLY", "SIX_HOURLY", "DAILY" and "WEEKLY". Called 'rollup' in queries.

Value Case Sensitive?

false

agentName

Display Name

Agent Name

Description

The agent name of the Flume Agent associated with this entity. Called 'agentName' in queries.

Value Case Sensitive?

true

componentName

Display Name

Component Name

Description

The component name of the Flume component associated with this entity. For example, if this entity is a Flume channel, the value of this attribute will be the channel's name. Called 'componentName' in queries.

Value Case Sensitive?

false

schedulerType

Display Name

Scheduler Type

Description

The YARN scheduler type of the YARN pool associated with this entity. Called 'schedulerType' in queries.

Value Case Sensitive?

false

solrCollectionName

Display Name

Solr Collection Name

Description

The name of the Solr collection associated with this entity. Called 'solrCollectionName' in queries.

Value Case Sensitive?

true

solrShardName

Display Name

Solr Shard Name

Description

The name of the Solr shard associated with this entity. Called 'solrShardName' in queries.

Value Case Sensitive?

true

solrReplicaName

Display Name

Solr Replica Name

Description

The name of the Solr replica associated with this entity. Called 'solrReplicaName' in queries.

Value Case Sensitive?

true

kafkaBrokerId

Display Name

Broker Id

Description

Id of a Kafka broker. Called 'kafkaBrokerId' in queries.

Value Case Sensitive?

false

kafkaClientId

Display Name

Client Id

Description

Id of a client. Called 'kafkaClientId' in queries.

Value Case Sensitive?

false

kafkaConnectConnectorName

Display Name

Kafka Connect Connector Name

Description

Kafka Connect Connector Name. Called 'kafkaConnectConnectorName' in queries.

Value Case Sensitive?

false

kafkaConnectConnectorTaskId

Display Name

Kafka Connect Connector Task Id

Description

Kafka Connect Connector Task Id. Called 'kafkaConnectConnectorTaskId' in queries.

Value Case Sensitive?

false

kafkaConsumerGroup

Display Name

Consumer Group

Description

Id of a Consumer Group. Called 'kafkaConsumerGroup' in queries.

Value Case Sensitive?

false

kafkaInternalTopic

Display Name

Is Internal Topic

Description

Topic is an internal Kafka topic. Called 'kafkaInternalTopic' in queries.

Value Case Sensitive?

false

kafkaLogDirectoryPath

Display Name

Log Directory Path

Description

Path of Kafka Log Directory. Called 'kafkaLogDirectoryPath' in queries.

Value Case Sensitive?

true

kafkaPartitionId

Display Name

Partition Id

Description

Id of a Kafka topic partition. Called 'kafkaPartitionId' in queries.

Value Case Sensitive?

false

kafkaTopicName**Display Name**

Topic Name

Description

Name for Kafka Topic. Called 'kafkaTopicName' in queries.

Value Case Sensitive?

true

kuduTableId**Display Name**

Table ID

Description

UUID for Kudu Table. Called 'kuduTableId' in queries.

Value Case Sensitive?

false

kuduTableName**Display Name**

Table Name

Description

Name for Kudu Table. Called 'kuduTableName' in queries.

Value Case Sensitive?

true

kuduTableState**Display Name**

Table State

Description

State for Kudu Table. Called 'kuduTableState' in queries.

Value Case Sensitive?

false

kuduTabletId**Display Name**

Tablet ID

Description

UUID for Kudu Tablet. Called 'kuduTabletId' in queries.

Value Case Sensitive?

false

kuduTabletState

Display Name

Tablet State

Description

State for Kudu Tablet. Called 'kuduTabletState' in queries.

Value Case Sensitive?

false

streams_replication_manager_herder_name

Display Name

SRM Distributed Herder Name

Description

SRM Distributed Herder Name. Called 'streams_replication_manager_herder_name' in queries.

Value Case Sensitive?

false

hive_on_tezTableName

Display Name

Table Name

Description

Name for Hive Table. Called 'hive_on_tezTableName' in queries.

Value Case Sensitive?

true