

## Ranger Auditing

Date published: 2019-11-01

Date modified:



# Legal Notice

© Cloudera Inc. 2024. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

# Contents

<b>Audit Overview.....</b>	<b>4</b>
<b>Managing Auditing with Ranger.....</b>	<b>4</b>
View audit details.....	4
Create a read-only Admin user (Auditor).....	7
<b>Ranger Audit Filters.....</b>	<b>8</b>
<b>Changing Ranger audit storage location and migrating data.....</b>	<b>13</b>

## Audit Overview

Apache Ranger provides a centralized framework for collecting access audit history and reporting data, including filtering on various parameters. Ranger enhances audit information obtained from Hadoop components and provides insights through this centralized reporting capability.

## Managing Auditing with Ranger

To explore options for auditing policies in Ranger, click Audit in the top menu.

Exclude Service Users : ☐

Entries : 1 to 25 of 149 Last Updated Time : 07/21/2019 12:24:11 PM

Policy ID	Policy Version	Event Time	Application	User	Service Name / Type	Resource Name / Type	Access Type	Result	Access Enforcer	Agent Host Name	Client IP	C
3	1	07/21/2019 12:21:35 PM	hbaseMaster	hbase	cm_hbase	hbase	balance	Allowed	ranger-acl	dhoyle-7-1-1.vpc.cloudera.com		C
3	1	07/21/2019 12:16:30 PM	hbaseMaster	hbase	cm_hbase	hbase	balance	Allowed	ranger-acl	dhoyle-7-1-1.vpc.cloudera.com		C
3	1	07/21/2019 12:11:30 PM	hbaseMaster	hbase	cm_hbase	hbase	balance	Allowed	ranger-acl	dhoyle-7-1-1.vpc.cloudera.com		C
3	1	07/21/2019 12:06:30 PM	hbaseMaster	hbase	cm_hbase	hbase	balance	Allowed	ranger-acl	dhoyle-7-1-1.vpc.cloudera.com		C

There are six tabs on the Audit page:

- Access
- Admin
- Login sessions
- Plugins
- Plugin Status
- User Sync

## View audit details

How to view operation details in Ranger audits.

### Procedure

To view details for a particular operation, click any tab, then Policy ID, Operation name, or Session ID.

## Audit > Admin: Update

Manage
Access Manager
Audit
Security Zone
Settings
Admin

Access
Admin
Login Sessions
Plugins
Plugin Status
User Sync

Entries : 1 to 25 of 70
Last Updated Time : 07/21/2019 01:06:40 PM

Operation	Audit Type	User	Date (Eastern Daylight Time)	Actions	Session Id
Service updated tag_service2	Ranger Service	admin	07/21/2019 01:09:34 PM	<span>Update</span>	40
Group created temp_employees	Ranger Group	admin	07/20/2019 02:15:05 PM	<span>Create</span>	38
Group created audit	Ranger Group	admin	07/18/2019 04:18:42 PM	<span>Create</span>	35
Exported policies	Ranger Policy	admin	07/17/2019 03:06:22 PM	<span>Export Json</span>	32
Service updated tag_service1	Ranger Service		07/15/2019 04:11:25 PM	<span>Update</span>	
Policy created EXPIRES_ON	Ranger Policy		07/15/2019 04:11:25 PM	<span>Create</span>	
Service created tag_tag	Ranger Service		07/15/2019 04:11:25 PM	<span>Create</span>	
Policy created					29
Service created					29
Security Zone					27
Policy created					27
Policy created					27
Policy created					27
Policy created					27
Security Zone					27
Policy created					27
Policy created					27
Policy created					27
Policy created					27
Policy created all - global	Ranger Policy	admin	07/14/2019 05:04:32 PM	<span>Create</span>	27
Policy created all - hiveservice	Ranger Policy	admin	07/14/2019 05:04:32 PM	<span>Create</span>	27
User created auditor1	Ranger User	admin	07/14/2019 05:02:58 PM	<span>Create</span>	27
Service updated cm_nifi_registry	Ranger Service		07/11/2019 11:30:39 AM	<span>Update</span>	
Policy created EXPIRES_ON	Ranger Policy		07/11/2019 11:30:39 AM	<span>Create</span>	

Operation : update

Name : tag\_service2

Date : 07/21/2019 01:09:34 PM Eastern Daylight Time

Updated By : admin

Service Details :

Fields	Old Value	New Value
Service Description	--	--
Service Name	tag_tag	tag_service2

OK

## Audit > Admin: Create

Ranger
Access Manager
Audit
Security Zone
Settings
admin

---

ACCESS | 
 Admin | 
 Login Sessions | 
 Plugins | 
 Plugin Status | 
 User Sync

Entries : 1 to 25 of 70 | Last Updated Time : 07/21/2019 01:09:40 PM

Operation	Audit Type	User	Date ( Eastern Daylight Time )	Actions	Session Id
Service updated <b>tag_service2</b>	Ranger Service	admin	07/21/2019 01:09:34 PM	<span style="background-color: #dce775; padding: 2px 5px;">Update</span>	40
Group created <b>temp_employees</b>	Ranger Group	admin	07/20/2019 02:15:05 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	38
Group created <b>audit</b>	Ranger Group	admin	07/18/2019 04:18:42 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	35
Exported policies	Ranger Policy	admin	07/17/2019 03:06:22 PM	<span style="background-color: #dce775; padding: 2px 5px;">Export Json</span>	32
Service updated <b>tag_service1</b>	Ranger Service		07/15/2019 04:11:25 PM	<span style="background-color: #dce775; padding: 2px 5px;">Update</span>	
Policy created <b>EXPIRES_ON</b>	Ranger Policy		07/15/2019 04:11:25 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	
Service created <b>tag_tag</b>	Ranger Service		07/15/2019 04:11:25 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	
Policy created <b>EXPIRES_ON</b>	Ranger Policy	admin	07/15/2019 04:11:24 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	29
Service created <b>tag_service1</b>	Ranger Service	admin	07/15/2019 04:11:24 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	29
Security Zone created <b>security-zone2</b>	Ranger Security Zone	admin	07/14/2019 05:24:36 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
Policy created all - database, udf	Ranger Policy	admin	07/14/2019 05:24:36 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
Policy created all - database, table, column	Ranger Policy	admin	07/14/2019 05:24:36 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
Policy created all - url	Ranger Policy	admin	07/14/2019 05:24:36 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
Policy created all - label	Ranger Policy	admin	07/14/2019 05:24:36 PM	<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	27
				<span style="background-color: #dce775; padding: 2px 5px;">Update</span>	
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	
				<span style="background-color: #dce775; padding: 2px 5px;">Create</span>	

**Operation : create**
×

Name : security-zone2  
 Date : 07/14/2019 05:24:36 PM Eastern Daylight Time  
 Created By : admin

**Zone Details :**

Fields :	New Value
Zone Description	--
Zone Audit User Groups	--
Zone Audit Users	auditor1
Zone Admin User Groups	--
Zone Admin Users	admin
Zone Tag Services	crm_tag
Zone Name	security-zone2

**Zone Service Details :**

Service Name	Zone Service Resources

OK

## Audit &gt; User Sync: Sync details

The screenshot shows the Ranger Admin console interface. At the top, there's a navigation bar with 'Ranger', 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. Below this, a tabbed interface shows 'Access', 'Admin', 'Login Sessions', 'Plugins', 'Plugin Status', and 'User Sync'. The 'User Sync' tab is active, displaying a search bar with 'START DATE: 07/21/2019' and a table of sync events. The table has columns for 'User Name', 'Sync Source', 'Number Of New Users', 'Number Of New Groups', 'Number Of Modified Users', 'Number Of Modified Groups', 'Event Time', and 'Sync Details'. A modal window titled 'Sync Details' is open, showing a list of configuration parameters and their values.

User Name	Sync Source	Number Of New		Number Of Modified		Event Time	Sync Details
		Users	Groups	Users	Groups		
rangerusersync	Unix	0	0	0	0	07/21/2019 01:22:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:21:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:20:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:19:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:18:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:17:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:16:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:15:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:14:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:13:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:12:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:11:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:10:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:09:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:08:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:07:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:06:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:05:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:04:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:03:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:02:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:01:48 PM	[Eye Icon]
rangerusersync	Unix	0	0	0	0	07/21/2019 01:00:47 PM	[Eye Icon]

**Sync Details**

Name	Value
Unix	nss
File Name	/etc/passwd
Sync time	07/21/2019 10:21:48 AM
Last modified time	12/31/1969 04:00:00 PM
Minimum user id	500
Minimum group id	0
Total number of users synced	35
Total number of groups synced	39

OK

## Create a read-only Admin user (Auditor)

Creating a read-only Admin user (Auditor) enables compliance activities because this user can monitor policies and audit events, but cannot make changes.


## About this task

When a user with the Auditor role logs in, they see a read-only view of Ranger policies and audit events. An Auditor can search and filter on access audit events, and access and view all tabs under Audit to understand access events. They cannot edit users or groups, export/import policies, or make changes of any kind.

## Procedure

1. Select Settings > Users/Groups/Roles.
2. Click Add New User.

3. Complete the **User Detail** section, selecting Auditor as the role:



The screenshot shows the Ranger web interface for creating a user. The top navigation bar includes 'Ranger', 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. The user 'admin' is logged in. The breadcrumb trail is 'Users/Groups/Roles > User Create'. The 'User Detail' section contains the following fields:

- User Name \*: auditor1
- New Password \*: [masked]
- Password Confirm \*: [masked]
- First Name \*: Audrey
- Last Name: [empty]
- Email Address: [empty]
- Select Role \*: Auditor (selected)
- Group: audit (with a '+' button to add more)

At the bottom of the form are 'Save' and 'Cancel' buttons.

4. Click Save.


## Ranger Audit Filters

You can use Ranger audit filters to control the amount of audit log data collected and stored on your cluster.

### About Ranger audit filters

Ranger audit filters allow you to control the amount of audit log data for each Ranger service. Audit filters are defined using a JSON string that is added to each service configuration. The audit filter JSON string is a simplified form of the Ranger policy JSON. Audit filters appear as rows in the Audit Filter section of the Edit Service view for each service. The set of audit filter rows defines the audit log policy for the service. For example, the default audit log policy for the Hadoop SQL service appears in the in the Ranger Admin web UI Service Manager Edit Service when you scroll down to Audit Filter. Audit filter is checked (visible) by default. In this example, the top row defines an audit filter that causes all instances of "access denied" to appear in audit logs. The lower row defines a filter that causes no metadata operations to appear in audit logs. These two filters comprise the default audit filter policy for the Hadoop SQL service.







Default audit filters

Default audit filters for the following Ranger service appear in the Edit Services and can then be modified as needed by Admin users.

HDFS service:



HBase service:



Hadoop SQL service:

Audit Filter:

Is Audited	Access Result	Resources	Operations	Permissions	Users	Groups	Roles	
Yes	DENIED	-- 	Type Action Name	Add Permissions 	Select User	Select Group	Select Role	
No	Select Value	-- 	⌘ METADATA OPERATION	Add Permissions 	Select User	Select Group	Select Role	

Knox service

Audit Filter:

Is Audited	Access Result	Resources	Operations	Permissions	Users	Groups	Roles	
Yes	DENIED	-- 	Type Action Name	Add Permissions 	Select User	Select Group	Select Role	
No	Select Value	-- 	Type Action Name	Add Permissions 	⌘ knox	Select Group	Select Role	

Solr service

Audit Filter:

Is Audited	Access Result	Resources	Operations	Permissions	Users	Groups	Roles	
Yes	DENIED	-- 	Type Action Name	Add Permissions 	Select User	Select Group	Select Role	
No	Select Value	-- 	Type Action Name	Add Permissions 	⌘ hive ⌘ hdfs ⌘ kafka ⌘ hbase ⌘ solr ⌘ rangeraz ⌘ knox ⌘ atlas	Select Group	Select Role	

Kafka service:

Audit Filter:

Is Audited	Access Result	Resources	Operations	Permissions	Users	Groups	Roles	
Yes	DENIED	-- 	Type Action Name	Add Permissions 	Select User	Select Group	Select Role	
No	Select Value	topic:ATLAS_ENTITIES, ATLAS_HOOK, ATLAS_SPARK_HOOK 	⌘ describe ⌘ publish ⌘ consume	Add Permissions 	⌘ atlas	Select Group	Select Role	
No	Select Value	topic:ATLAS_HOOK 	⌘ publish ⌘ describe	Add Permissions 	⌘ hive ⌘ hbase ⌘ impala ⌘ nifi	Select Group	Select Role	
No	Select Value	topic:ATLAS_ENTITIES 	⌘ consume ⌘ describe	Add Permissions 	⌘ rangertagsync	Select Group	Select Role	
No	Select Value	consumergroup:* 	⌘ consume	Add Permissions 	⌘ atlas ⌘ rangertagsync	Select Group	Select Role	
No	Select Value	-- 	Type Action Name	Add Permissions 	⌘ kafka	Select Group	Select Role	

KMS service

Audit Filter:

Is Audited	Access Result	Resources	Operations	Permissions	Users	Groups	Roles	
Yes	DENIED	-- 	Type Action Name	Add Permissions 	Select User	Select Group	Select Role	
No	Select Value	-- 	⌘ read	Add Permissions 	⌘ keyadmin	Select Group	Select Role	

Atlas service

Audit Filter:

Is Audited	Access Result	Resources	Operations	Permissions	Users	Groups	Roles	
Yes	DENIED	-- 	Type Action Name	Add Permissions 	Select User	Select Group	Select Role	
No	Select Value	-- 	Type Action Name	Add Permissions 	⌘ atlas	Select Group	Select Role	

Ozone service

Audit Filter:

Is Audited	Access Result	Resources	Operations	Permissions	Users	Groups	Roles	
Yes	DENIED	-- 	Type Action Name	Add Permissions 	Select User	Select Group	Select Role	
No	Select Value	-- 	Type Action Name	Add Permissions 	⌘ om	Select Group	Select Role	

Tag-based service

Is Audited	Access Result	Resources	Operations	Permissions	Users	Groups	Roles
Yes ▾	DENIED x ▾	-- + -	Type Action Name	Add Permissions +	Select User	Select Group	Select Role

Default audit filter policies do not exist for Yarn, NiFi, NiFi Registry, Kudu, or schema registry services.

## Ranger audit filter policy configuration

To configure an audit filter policy, click the Edit icon for either a resource-, or tag-based service in the Ranger Admin web UI. You configure a Ranger audit filter policy by adding (+), deleting (X), or modifying each audit filter row for the service. The preceding example shows the Add and Delete icons for each filter row. To configure each filter in the policy, use the controls in the filter row to edit filter properties. For example, you can configure:

### Is Audited: choose Yes or No

to include or not include a filter in the audit logs for a service

### Access Result: choose DENIED, ALLOWED, or NOT\_DETERMINED

to include that access result in the audit log filter

### Resources: Add or Delete a resource item

to include or remove the resource from the audit log filter

### Operations: Add or Remove an action name

to include the action/operation in the audit log filter

(click x to remove an existing operation)

### Permissions: Add or Remove permissions

1. Click + in Permissions to open the Add dialog.
2. Select/Unselect required permissions.

For example, in HDFS service select read, write, execute, or All permissions.

### Users: click Select User to see a list of defined users

to include one or multiple users in the audit log filter

### Groups: click Select Group to see a list of defined groups

to include one or multiple groups in the audit log filter

### Roles: click Select Role to see a list of defined roles

to include one or multiple roles in the audit log filter

### Audit filter details

- When you save the UI selections described in the preceding list, audit filters are defined as a JSON list. Each service references a unique list.
- For example, ranger.plugin.audit.filters for the HDFS service includes:

```
[
  {
    "accessResult": "DENIED",
    "isAudited": true
  },
  {
    "users": [
      "unaudited-user1"
    ],
    "groups": [
      "unaudited-group1"
    ],
    "roles": [
      "unaudited-role1"
    ]
  }
]
```

```

    "isAudited":false
  },
  {
    "actions":[
      "listStatus",
      "getFileinfo"
    ],
    "accessTypes":[
      "execute"
    ],
    "isAudited":false
  },
  {
    "resources":{
      "path":{
        "values":[
          "/audited"
        ],
        "isRecursive":true
      }
    },
    "isAudited":true
  },
  {
    "resources":{
      "path":{
        "values":[
          "/unaudited"
        ],
        "isRecursive":true
      }
    },
    "isAudited":false
  }
]

```

- Each value in the list is an audit filter, which takes the format of a simplified Ranger policy, along with access results fields.
- Audit filters are defined with rules on Ranger policy attributes and access result attributes.
  - Policy attributes: resources, users, groups, roles, accessTypes
  - Access result attributes: isAudited, actions, accessResult
- The following audit filter specifies that accessResult=DENIED will be audited.

The isAudited flag specifies whether or not to audit.

```
{ "accessResult": "DENIED", "isAudited": true }
```

- The following audit filter specifies that “resource => /unaudited” will not be audited.

```
{ "resources": { "path": { "values": [ "/unaudited" ], "isRecursive": true } }, "isAudited": false }
```

- The following audit filter specifies that access to resource database=> sys table=> dump by user “use2” will not be audited.

```
{ "resources": { "database": { "values": [ "sys" ] }, "table": { "values": [ "dump" ] } }, "users": [ "user2" ], "isAudited": false }
```

- The following audit filter specifies that access result in actions => listStatus, getFileinfo and accessType => execute will not be audited.

```
{ "actions": [ "listStatus", "getFileinfo" ], "accessTypes": [ "execute" ], "isAudited": false }
```

- The following audit filter specifies that access by user "superuser1" and group "supergroup1" will not be audited.

```
{"users":["superuser1"],"groups":["supergroup1"],"isAudited":false}
```

- The following audit filter specifies that access to any resource tagged as NO\_AUDIT will not be audited.

```
{"resources":{"tag":{"values":["NO_AUDIT"]}},"isAudited":false}
```

## Changing Ranger audit storage location and migrating data

How to change the location of existing and future Ranger audit data collected by Solr from HDFS to local or from local to HDFS.

### Before you begin

- Stop Atlas from Cloudera Manager.
- If using Kerberos, set the SOLR\_PROCESS\_DIR environment variable.

```
# export SOLR_PROCESS_DIR=$(ls -ldtr /var/run/cloudera-scm-agent/process/  
*SOLR_SERVER | tail -1)
```

### About this task

Starting with Cloudera Runtime version 7.1.4 / 7.2.2, the storage location for ranger audit data collected by Solr changed to local file system from HDFS, as was true for previous versions. The default storage location Ranger audit data storage location for Cloudera Runtime-7.1.4+ and Cloudera Runtime-7.2.2+ installations is local file system. After upgrading from an earlier Cloudera platform version, follow these steps to backup and migrate your Ranger audit data and change the location where Solr stores your future Ranger audit records.

- The default value of the index storage in the local file system is /var/lib/solr-infra. You can configure this, using Cloudera Manager Solr Configuration "Solr Data Directory" .
- The default value of the index storage in HDFS is /solr-infra. You can configure this, using Cloudera Manager Solr Configuration "HDFS Data Directory" .

### Procedure

1. Create HDFS Directory to store the collection backups.

As an HDFS super user, run the following commands to create the backup directory:

```
# hdfs dfs -mkdir /solr-backups  
# hdfs dfs -chown solr:solr /solr-backups
```

2. Obtain valid kerberos ticket for Solr user.

```
# kinit -kt solr.keytab solr/$(hostname -f)
```

3. Download the configs for the collection.

```
# solrctl instancedir --get ranger_audits /tmp/ranger_audits  
# solrctl instancedir --get atlas_configs /tmp/atlas_configs
```

4. Modify the solrconfig.xml for each of the configs for which data needs to be stored in HDFS.

In /tmp/<config\_name>/conf created during Step 3., edit properties in the solrconfig.xml file as follows:

- When migrating your data storage location from local file system to HDFS, replace these two lines:

```
<directoryFactory name="DirectoryFactory"  
class="${solr.directoryFactory:solr.NRTCachingDirectoryFactory}">
```

```
<lockType>${solr.lock.type:native}</lockType>
```

with

```
<directoryFactory name="DirectoryFactory"
  class="${solr.directoryFactory:org.apache.solr.core.HdfsDirectoryFactory}">
```

```
<lockType>${solr.lock.type:hdfs}</lockType>
```

- When migrating your data storage location from HDFS to local file system, replace these two lines:

```
<directoryFactory name="DirectoryFactory"
  class="${solr.directoryFactory:org.apache.solr.core.HdfsDirectoryFactory}">
```

```
<lockType>${solr.lock.type:hdfs}</lockType>
```

with

```
<directoryFactory name="DirectoryFactory"
  class="${solr.directoryFactory:solr.NRTCachingDirectoryFactory}">
```

```
<lockType>${solr.lock.type:native}</lockType>
```

##### 5. Update the modified configs in Zookeeper.

```
# solrctl --jaas $SOLR_PROCESS_DIR/jaas.conf instancedir --update
  atlas_configs /tmp/atlas_configs
```

```
# solrctl --jaas $SOLR_PROCESS_DIR/jaas.conf instancedir --update
  ranger_audits /tmp/ranger_audits
```

##### 6. Backup the Solr collections.

- When migrating your data storage location from local file system to HDFS, run:

```
# curl -k --negotiate -u : "https://$(hostname
  -f):8995/solr/admin/collections?action=BACKUP&name=vertex_backup&col
  lection=vertex_index&
  location=hdfs://<Namenode_Hostname>:8020/solr-backups"
```

In the preceding command, the important points are name, collection, and location:

###### **name**

specifies the name of the backup. It should be unique per collection

###### **collection**

specifies the collection name for which the backup will be performed

###### **location**

specifies the HDFS path, where the backup will be stored

Repeat the curl command for different collections, modifying the parameters as necessary for each collection.

The expected output would be -

```
"responseHeader": {
  "status": 0,
  "QTime": 10567,
  "success": {
    "Solr_Server_Hostname:8995_solr": {
      "responseHeader": {
        "status": 0,
```

```
"QTime":8959}}}}
```

- When migrating your data storage location from HDFS to local file system:

Refer to Back up a Solr collection for specific steps, and make the following adjustments:

- If TLS is enabled for the Solr service, specify the trust store and password by using the ZKCLI\_JVM\_FLAGS environment variable before you begin the procedure.

```
# export ZKCLI_JVM_FLAGS="-Djavax.net.ssl.trustStore=/path/to/truststore.jks -Djavax.net.ssl.trustStorePassword="
```

- Create Snapshot

```
# solrctl --jaas $SOLR_PROCESS_DIR/jaas.conf collection --create-snapshot <snapshot_name> -c <collection_name>
```

- or use the Solr API to take the backup:

```
curl -i -k --negotiate -u : "https://(hostname -f):8995/solr/admin/collections?action=BACKUP&name=ranger_audits_bkp&collection=ranger_audits&location=/path/to/solr-backups"
```

- Export Snapshot

```
# solrctl --jaas $SOLR_PROCESS_DIR/jaas.conf collection --export-snapshot <snapshot_name> -c <collection_name> -d <destination_directory>
```



**Note:** The <destination\_directory> is a HDFS path. The ownership of this directory should be solr:solr.

## 7. Delete the collections from the original location.

All instances of Solr service should be up, running, and healthy before deleting the collections. Use Cloudera Manager to check for any alerts or warnings for any of the instances. If alerts or warnings exist, fix those before deleting the collection.

```
# solrctl collection --delete edge_index
# solrctl collection --delete vertex_index
# solrctl collection --delete fulltext_index
# solrctl collection --delete ranger_audits
```

## 8. Verify that the collections are deleted from the original location.

```
# solrctl collection --list
```

This will give an empty result.

## 9. Verify that no leftover directories for any of the collections have been deleted.

- When migrating your data storage location from local file system to HDFS:

```
# cd /var/lib/solr-infra
```

Get the value of "Solr Data Directory, using Cloudera Manager Solr Configuration .

```
# ls -ltr
```

- When migrating your data storage location from HDFS to local file system, replace these two lines:

```
# hdfs dfs -ls /solr/<collection_name>
```



**Note:** If any directory name which starts with the collection name deleted in Step 7. exists, delete/ move the directory to another path.

**10. Restore the collection from backup to the new location.**

Refer to [Restore a Solr collection](#), for more specific steps.

```
# curl -k --negotiate -u : "https://$(hostname -f):8995/solr/admin/collections?
action=RESTORE&name=<Name_of_backup>&location=hdfs:/
<Namenode_Hostname>:8020/solr-backups&collection=<Collection_Name>"
```

```
# solrctl collection --restore ranger_audits
-l hdfs://<Namenode_Hostname>:8020/solr-backups
-b ranger_backup -i ranger1
```

The request id must be unique for each restore operation, as well as for each retry.

To check the status of restore operation:

```
# solrctl collection --request-status <requestId>
```



**Note:** If the Atlas Collections (vertex\_index, fulltext\_index and edge\_index) restore operations fail, restart the solr service and rerun the restore command. Now, the restart operations should complete successfully.

**11. Verify the Atlas & Ranger functionality.**

Verify that both Atlas and Ranger audits functions properly, and that you can see the latest audits in Ranger Web UI and latest lineage in Atlas.

- To verify Atlas audits, create a test table in Hive, and then query the collections to see if you are able to view the data.
- You can also query the collections every 20-30 seconds (depending on how other services utilize Atlas/Ranger), and verify if the "numDocs" value increases at every query.

```
# curl -k --negotiate -u : "https://$(hostname -f):8995/solr/edge_index/
select?q=%3A*&wt=json&ident=true&rows=0"
# curl -k --negotiate -u : "https://$(hostname -f):8995/solr/vertex_index/
select?q=%3A*&wt=json&ident=true&rows=0"
# curl -k --negotiate -u : "https://$(hostname -f):8995/solr/
fulltext_index/select?q=%3A*&wt=json&ident=true&rows=0"
# curl -k --negotiate -u : "https://$(hostname -f):8995/solr/
ranger_audits/select?q=%3A*&wt=json&ident=true&rows=0"
```