

## Authorization reference

Date published: 2020-07-28

Date modified: 2021-12-13



# Legal Notice

© Cloudera Inc. 2024. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

# Contents

<b>Migrating from Sentry to Ranger.....</b>	<b>4</b>
<b>Check MySQL isolation configuration.....</b>	<b>5</b>
<b>Ranger audit schema reference.....</b>	<b>5</b>
<b>Ranger database schema reference.....</b>	<b>5</b>
<b>Ranger policies allowing create privilege for Hadoop_SQL databases.....</b>	<b>6</b>
<b>Ranger policies allowing create privilege for Hadoop_SQL tables.....</b>	<b>7</b>
<b>Access required to Read/Write on Hadoop_SQL tables using SQL.....</b>	<b>8</b>
<b>Mapping Sentry permissions for Solr to Ranger policies.....</b>	<b>8</b>

## Migrating from Sentry to Ranger

Before deciding to migrate from Sentry to Ranger, read the Sentry to Ranger Concise Guide and the topics in this guide.

The [Sentry to Ranger Concise Guide blog post](#) describes fundamental differences between Sentry and Ranger, compares the two products, and provides additional information that helps prepare you for your migration.

Read the topics in this section for information about preparing to migrate Sentry permissions to Ranger policies and topics that describe how to migrate once you are ready.

Sentry (CDH) had an object ownership feature, which added ownership permissions for all the databases/tables created. This feature was added in CDH-5.16 and supported through CDH-6.2. After enabling the ownership feature Sentry would grant owner permission for all the databases/tables created after enablment.

### Ranger default policies for Hadoop Sql

Policy Name	User	Permissions
all - database, table, column	{OWNER}	all permissions
all - database, table	{OWNER}	all permissions
all - database, udf	{OWNER}	all permissions
all - database	{OWNER}	all permissions

After migration from Sentry:

- All the users who have {OWNER} permissions on objects, such as databases/tables, will get All the permissions from above default Ranger policies.
- Above Ranger policies will be applicable only to objects for whom they are the owner.
- Even if Sentry does not have owner mapping, in other words, the ownership feature is disabled, this scenario holds true.



**Note:** If you are using MySQL as the Ranger database and seeing the following error while migrating from Sentry to Ranger:

**Error:**

```
com.mysql.cj.jdbc.exceptions.MySQLTransactionRollbackException: Lock wait timeout exceeded; try restarting transaction
```

### Resolution

1. In Cloudera Manager Configuration Search , type core-site.xml, then click Search.
2. In CORE\_SETTINGS-1 (Service-Wide), in Name, type ranger.client.pool.size.
3. In Value, type 1.
4. Click Save Changes (CTRL+S).
5. On the Cluster Actions , click Restart.

## Check MySQL isolation configuration

Before migrating a MySQL database for CDH Sentry to CDP Ranger, you must check and set isolation configuration to READ-COMMITTED.

### Before you begin

CDP Ranger MySQL database must have isolation set to READ-COMMITTED.

### About this task

You must check the isolation configuration of the MySQL database used for CDH Sentry before migrating to Ranger. IF the isolation configuration for CDH Sentry setting is REPEATABLE-READ, you must change the isolation setting to READ-COMMITTED.

### Procedure

1. Log in to MySQL server.
2. Run the following query:

```
SELECT @@GLOBAL.tx_isolation, @@tx_isolation, @@session.tx_isolation;
```

- a) If the query output is:

```
-----
--
@@GLOBAL.tx_isolation | @@tx_isolation | @@session.tx_isolation
-----
REPEATABLE-READ | REPEATABLE-READ | REPEATABLE-READ
```

- b) Then, set the isolation to READ-COMMITTED, using the following query:

```
mysql> SET tx_isolation = 'READ-COMMITTED';
Query OK, 0 rows affected (0.00 sec)

mysql> SET GLOBAL tx_isolation = 'READ-COMMITTED';
Query OK, 0 rows affected (0.00 sec)
```

## Ranger audit schema reference

See the following link to the current version of the Ranger Audit Schema:

Ranger Audit Schema: <https://cwiki.apache.org/confluence/display/RANGER/Ranger+Audit+Schema#RangerAuditSchema-AudittoHDFS>

## Ranger database schema reference

See the following links to versions of the Ranger Database Schema:

Ranger v2.0.0 : <https://cwiki.apache.org/confluence/display/RANGER/Ranger+2.0.0+Database+Schema>

Ranger v2.1.0 : <https://cwiki.apache.org/confluence/display/RANGER/Ranger+2.1.0+Database+Schema>

Ranger v2.2.0 : <https://cwiki.apache.org/confluence/display/RANGER/Ranger+2.2.0+Database+Schema>

## Ranger policies allowing create privilege for Hadoop\_SQL databases

Users with authorized access through Ranger policies in Hadoop SQL with at least one of the following permissions can create databases.

In CDP, an authorized user can create Hadoop\_SQL databases with or without specifying location. If you do not specify location, then the database is created in the default HDFS location used by Hadoop\_SQL. If you specify location, then the database is created in the HDFS location you specify.

- A user creating databases with location clauses requires one of the following additional access:
  - direct read and write access to the HDFS location
  - a Ranger Hadoop\_SQL URL policy that provides the user all permissions on the HDFS location
- A hive user creating databases with location clauses must have all permissions on the HDFS location using one of the following:
  - an appropriate HDFS POSIX permission
  - HDFS ACL
  - HDFS Ranger policy



**Note:** If you choose to use an HDFS Ranger policy for this purpose, make sure to refer to the HDFS location in the Ranger policy using a path, such as: /databases/sample/username, not a URL, such as: hdfs://nameservice1/databases/sample/username .

**Table 1: Permissions allowing a user to create a database**

User	Permission	Database	Table	Column	UDF
hive and impala	all	all (database=*)			
		all (database=*)	all (table=*)		
		all (database=*)	all (table=*)	all (column=*)	
		all (database=*)			udf=*
hive and impala	create	all (database=*)			
		all (database=*)	all (table=*)		
		all (database=*)	all (table=*)	all (column=*)	
		all (database=*)			udf=*



**Note:**

- For use-cases where only create access is provided and drop access is not provided explicitly, the user might implicitly get a few other permissions through the default policies added (unless the default policies are modified).
- The default all database and all database, table policy usually would list {OWNER} as an authorized user.
- Removing {OWNER} from these default policies would restrict access to users with specific permissions listed explicitly in policies. Removing {OWNER} is not recommended. Proceed with caution when considering such an action.

### Related Information

[Resource-based Services and Policies](#)

## Ranger policies allowing create privilege for Hadoop\_SQL tables

Users with authorized access through Ranger policies in Hadoop SQL with at least one of the following permissions can create external or managed tables on the corresponding database(s) listed in the policy.

- A user creating external tables with location clauses requires one of the following additional access:
  - direct read and write access to the HDFS location
  - a Ranger Hadoop\_SQL URL policy that provides the user read and write permissions on the HDFS location
- A user creating external tables with location clauses must have read and write permissions on the HDFS location using one of the following:
  - an appropriate HDFS POSIX permission
  - HDFS ACL
  - HDFS Ranger policy



**Note:** If you choose to use an HDFS Ranger policy for this purpose, make sure to refer to the HDFS location in the Ranger policy using a path, such as: /databases/sample/username, not a URL, such as: hdfs://nameservice1/databases/sample/username . Make sure that the URL defined in Ranger does not have a trailing /.

**Table 2: Permissions allowing a user to create a table**

User	Permission	Database	Table	Column	UDF
hive and impala	all	database=* or <database name>			
		database=* or <database name>	all (table=*)		
		database=* or <database name>	all (table=*)	all (column=*)	
		database=* or <database name>			udf=*
hive and impala	create	database=* or <database name>			
		database=* or <database name>	all (table=*)		
		database=* or <database name>	all (table=*)	all (column=*)	
		database=* or <database name>			udf=*

**Note:**

- For use-cases where only create access is provided and drop access is not provided explicitly, the user might implicitly get a few other permissions through the default policies added (unless the default policies are modified).
- The default all database and all database, table policy usually would list {OWNER} as an authorized user.
- For these use-cases where only permissions were provided at the database and udf levels, the user may still be able to create tables due to the reasons specified above.
- Removing {OWNER} from these default policies would restrict access to users with specific permissions listed explicitly in policies. Removing {OWNER} is not recommended. Proceed with caution when considering such an action.
- Any managed table creation using an external location would fail with the following error: A managed table's location should be located within managed warehouse root directory or within its database's managedLocationUri.

**Related Information**[Resource-based Services and Policies](#)

## Access required to Read/Write on Hadoop\_SQL tables using SQL

Users with authorized access through Ranger policies in Hadoop SQL with at least one of the following permissions can read and write to external or managed Hadoop\_SQL tables using SQL syntax.

- Any user who created a managed or an external table {owner} can select and insert data in the table, provided the permissions for database, table and columns are present in Hadoop\_SQL service within Ranger.
- Any user with select privileges on columns, tables and databases in Hadoop\_SQL service within Ranger can read data from managed or external tables by executing SQL statements.
- Any user with update privileges on columns, tables and databases in Hadoop\_SQL service within Ranger can write data into Managed or External Tables by executing SQL statements.

**Related Information**[Resource-based Services and Policies](#)

## Mapping Sentry permissions for Solr to Ranger policies

Use the mapping reference table to create Ranger policies that reflect the privileges defined for Solr in your Sentry permissions.

Sentry has the following objects for Solr:

- admin
- collection
- config
- schema

The admin object type controls access to administrative actions through the following privilege objects:

- collection
- cores
- security
- metrics



- autoscaling

Ranger has only one object right now, which is collection. Permissions for collections are of type:

- SolrAdmin
- Query
- Update
- Other

**Table 3: Ranger policies required to set equivalent access that Sentry privileges allowed**

Sentry privilege	Ranger policy
Collections	
admin=collections - action=UPDATE collection=<aliasName> - action=UPDATE	All collections - permission SolrAdmin
admin=collections - action=UPDATE collection=<collectionName> - action=UPDATE	Policy for <collectionName>, permissions: SolrAdmin
admin=collections - action=UPDATE	All collections - permissions: SolrAdmin
admin=collections - action=QUERY collection=<collectionName> - action=QUERY	Policy for <collectionName> - permissions: SolrAdmin
Cores	
admin=cores - action=UPDATE collection=<coreName> - action=UPDATE	All collections - permission: SolrAdmin
admin=cores - action=QUERY collection=<coreName> - action=QUERY	All collections - permission: SolrAdmin
Configs	
config=<configName> - action=*	All collections = permission: SolrAdmin
Non-Administrative	
collection=<collectionName> - action=QUERY	Policy for <collectionName> - permissions: Query, Others
collection=<collectionName> - action=UPDATE	Policy for <collectionName> - permissions: Update