

Cloudera Runtime 7.0.0

## Developing Applications with Apache Kudu

Date published: 2019-08-21

Date modified:

# CLOUDERA

<https://docs.cloudera.com/>

# Legal Notice

© Cloudera Inc. 2025. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

# Contents

<b>Developing applications with Apache Kudu.....</b>	<b>4</b>
Viewing the API documentation.....	4
Kudu example applications.....	4
Maven artifacts.....	5
Building the Java client.....	5
Kudu Python client.....	5
Example Apache Impala commands with Kudu.....	6
Kudu integration with Spark.....	6
Upsert option in Kudu Spark.....	8
Using Spark with a secure Kudu cluster.....	9
Spark integration known issues and limitations.....	9
Spark integration best practices.....	9

# Developing applications with Apache Kudu

Apache Kudu provides C++ and Java client APIs, as well as reference examples to illustrate their use.



**Warning:** Use of server-side or private interfaces is not supported, and interfaces which are not part of public APIs have no stability guarantees.

## Viewing the API documentation

This topic provides you information on how to find the API documentation for C++ and Java.

### C++ API Documentation

The documentation for the C++ client APIs is included in the header files in `/usr/include/kudu/` if you installed Kudu using packages or subdirectories of `src/kudu/client/` if you built Kudu from source. If you installed Kudu using parcels, no headers are included in your installation, and you will need to build Kudu from source in order to have access to the headers and shared libraries.

The following command is a naive approach to finding relevant header files. Use of any APIs other than the client APIs is unsupported.

```
find /usr/include/kudu -type f -name *.h
```

### Java API Documentation

View the *Java API documentation* online. Alternatively, after building the Java client, Java API documentation is available in `java/kudu-client/target/apidocs/index.html`.

## Kudu example applications

Several example applications are provided in the examples directory of the Apache Kudu git repository. Each example includes a README that shows how to compile and run it. The following list includes some of the examples that are available today. Check the repository itself in case this list goes out of date.

### cpp/example.cc:

A simple C++ application which connects to a Kudu instance, creates a table, writes data to it, then drops the table.

### java/java-example:

A simple Java application which connects to a Kudu instance, creates a table, writes data to it, then drops the table.

### java/insert-loadgen:

A small Java application which listens on a TCP socket for time series data corresponding to the Collectl wire protocol. The commonly-available collectl tool can be used to send example data to the server.

### python/dstat-kudu:

A Java application that generates random insert load.

### python/graphite-kudu:

An example program that shows how to use the Kudu Python API to load data into a new / existing Kudu table generated by an external program, dstat in this case.

**python/graphite-kudu:**

An example plugin for using graphite-web with Kudu as a backend.

These examples should serve as helpful starting points for your own Kudu applications and integrations.

## Maven artifacts

The following Maven `<dependency>` element is valid for the Apache Kudu GA release:

```
<dependency>
  <groupId>org.apache.kudu</groupId>
  <artifactId>kudu-client</artifactId>
  <version><kudu-cdp-version></version>
</dependency>
```

For `<kudu-cdp-version>`, check *Cloudera Runtime component versions* in *Release Notes*.

Convenience binary artifacts for the Java client and various Java integrations (e.g. Spark, Flume) are also now available via the *ASF Maven repository* and the *Central Maven repository*.

## Building the Java client

This topic contains the list of requirements and the command to build the Java client.

### Requirements

- JDK 7
- protoc 2.6 or newer installed in your path, or built from the `thirdparty/` directory. Run the following commands to build protoc from the third-party dependencies:

```
thirdparty/download-thirdparty.sh
thirdparty/build-thirdparty.sh protobuf
```

To build the Java client, clone the Kudu Git repository, change to the `java` directory, and issue the following command:

```
./gradlew :kudu-client:assemble -x test
```

For more information about building the Java API, as well as Eclipse integration, see `java/README.md`.

## Kudu Python client

The Kudu Python client provides a Python friendly interface to the C++ client API. To install and use Kudu Python client, you need to install the Kudu C++ client libraries and headers.

### Procedure

1. Install Cython: `sudo pip install cython`.
2. Download the Kudu Python client from [kudu-python](#): `kudu-python-1.2.0.tar.gz`.
3. Install kudu-python: `sudo pip install kudu-python`.

The following sample demonstrates the use of part of the Python client:

```
import kudu
from kudu.client import Partitioning
from datetime import datetime
```

```

# Connect to Kudu master server
client = kudu.connect(host='kudu.master', port=7051)

# Define a schema for a new table
builder = kudu.schema_builder()
builder.add_column('key').type(kudu.int64).nullable(False).primary_key()
builder.add_column('ts_val', type_=kudu.unixtime_micros, nullable=False,
    compression='lz4')
schema = builder.build()

# Define partitioning schema
partitioning = Partitioning().add_hash_partitions(column_names=['key'],
    num_buckets=3)

# Create new table
client.create_table('python-example', schema, partitioning)

# Open a table
table = client.table('python-example')

# Create a new session so that we can apply write operations
session = client.new_session()

# Insert a row
op = table.new_insert({'key': 1, 'ts_val': datetime.utcnow()})
session.apply(op)
# Upsert a row
op = table.new_upsert({'key': 2, 'ts_val': "2016-01-01T00:00:00.000000"})
session.apply(op)
# Updating a row
op = table.new_update({'key': 1, 'ts_val': ("2017-01-01", "%Y-%m-%d")})
session.apply(op)
# Delete a row
op = table.new_delete({'key': 2})
session.apply(op)
# Flush write operations, if failures occur, capture print them.
try:
    session.flush()
except kudu.KuduBadStatus as e:
    print(session.get_pending_errors())

# Create a scanner and add a predicate
scanner = table.scanner()
scanner.add_predicate(table['ts_val'] == datetime(2017, 1, 1))
# Open Scanner and read all tuples
# Note: This doesn't scale for large scans
result = scanner.open().read_all_tuples()

```

## Example Apache Impala commands with Kudu

See *Using Apache Impala with Kudu* for guidance on installing and using Impala with Kudu, including several impala-shell examples.

### Related Information

[Impala integration limitations](#)

## Kudu integration with Spark

Kudu integrates with Spark through the Data Source API as of version 1.0.0. Include the kudu-spark dependency using the `--packages` option.

Use the `kudu-spark_2.10` artifact if using Spark with Scala 2.10. Note that Spark 1 is no longer supported in Kudu starting from version 1.6.0. So in order to use Spark 1 integrated with Kudu, version 1.5.0 is the latest to go to.

```
spark-shell --packages org.apache.kudu:kudu-spark_2.10:1.5.0-cdh5.13.91 --repositories https://repository.cloudera.com/artifactory/cloudera-repos/
```

Use `kudu-spark2_2.11` artifact if using Spark 2 with Scala 2.11.



**Note:** kudu-spark versions 1.8.0 and below have slightly different syntax. See the documentation of your version for a valid example. Versioned documentation can be found on the [releases page](#).

```
spark2-shell --packages org.apache.kudu:kudu-spark2_2.11:1.9.0-cdh6.2.0 --repositories https://repository.cloudera.com/artifactory/cloudera-repos/
```

Below is a minimal Spark SQL "select" example for a Kudu table created with Impala in the "default" database. We first import the kudu spark package, then create a DataFrame, and then create a view from the DataFrame. After those steps, the table is accessible from Spark SQL.

```
import org.apache.kudu.spark.kudu._
// Create a DataFrame that points to the Kudu table we want to query.
val df = spark.read.options(Map("kudu.master" -> "master1.foo.com,master2.foo.com,master3.foo.com",
                                "kudu.table" -> "default.my_table")).kudu
// Create a view from the DataFrame to make it accessible from Spark SQL.
df.createOrReplaceTempView("my_table")
// Now we can run Spark SQL queries against our view of the Kudu table.
spark.sql("select * from my_table").show()
```

Below is a more sophisticated example that includes both reads and writes:

```
import org.apache.kudu.spark.kudu._
import org.apache.kudu.client._
import collection.JavaConverters._

// Read a table from Kudu
val df = spark.read
  .options(Map("kudu.master" -> "kudu.master:7051", "kudu.table" -> "kudu_table"))
  .format("kudu").load
// Query using the Spark API...
df.select("id").filter("id >= 5").show()

// ...or register a temporary table and use SQL
df.createOrReplaceTempView("kudu_table")
val filteredDF = spark.sql("select id from kudu_table where id >= 5").show()

// Use KuduContext to create, delete, or write to Kudu tables
val kuduContext = new KuduContext("kudu.master:7051", spark.sparkContext)

// Create a new Kudu table from a DataFrame schema
// NB: No rows from the DataFrame are inserted into the table
kuduContext.createTable(
  "test_table", df.schema, Seq("key"),
  new CreateTableOptions()
    .setNumReplicas(1)
    .addHashPartitions(List("key").asJava, 3))

// Insert data
kuduContext.insertRows(df, "test_table")

// Delete data
```

```

kuduContext.deleteRows(filteredDF, "test_table")

// Upsert data
kuduContext.upsertRows(df, "test_table")
// Update data
val alteredDF = df.select("id", $"count" + 1)
kuduContext.updateRows(filteredRows, "test_table")

// Data can also be inserted into the Kudu table using the data source, though the methods on
// KuduContext are preferred
// NB: The default is to upsert rows; to perform standard inserts instead,
// set operation = insert
// in the options map
// NB: Only mode Append is supported

df.write
  .options(Map("kudu.master" -> "kudu.master:7051", "kudu.table" -> "test_table"))
  .mode("append")
  .format("kudu").save

// Check for the existence of a Kudu table
kuduContext.tableExists("another_table")

// Delete a Kudu table
kuduContext.deleteTable("unwanted_table")

```

## Upsert option in Kudu Spark

The upsert operation in kudu-spark supports an extra write option of ignoreNull. If set to true, it will avoid setting existing column values in Kudu table to Null if the corresponding DataFrame column values are Null. If unspecified, ignoreNull is false by default.

```

val dataframe = spark.read
  .options(Map("kudu.master" -> "kudu.master:7051", "kudu.table" -> simpleTableName))
  .format("kudu").load
dataframe.createOrReplaceTempView(simpleTableName)
dataframe.show()

// Below is the original data in the table 'simpleTableName'
+----+----+
|key|val|
+----+----+
|  0|foo|
+----+----+

// Upsert a row with existing key 0 and val Null with ignoreNull set to true
val nullDF = spark.createDataFrame(Seq((0, null.asInstanceOf[String]))).toDF("key", "val")
val wo = new KuduWriteOptions
wo.ignoreNull = true
kuduContext.upsertRows(nullDF, simpleTableName, wo)
dataframe.show()
// The val field stays unchanged
+----+----+
|key|val|
+----+----+
|  0|foo|
+----+----+

```



```
// Upsert a row with existing key 0 and val Null with ignoreNull default/set
// to false
kuduContext.upsertRows(nullDF, simpleTableName)
// Equivalent to:
// val wo = new KuduWriteOptions
// wo.ignoreNull = false
// kuduContext.upsertRows(nullDF, simpleTableName, wo)
df.show()
// The val field is set to Null this time
+---+---+
|key| val|
+---+---+
|  0|null|
+---+---+
```

## Using Spark with a secure Kudu cluster

The Kudu-Spark integration is able to operate on secure Kudu clusters which have authentication and encryption enabled, but the submitter of the Spark job must provide the proper credentials. For Spark jobs using the default 'client' deploy mode, the submitting user must have an active Kerberos ticket granted through kinit. For Spark jobs using the 'cluster' deploy mode, a Kerberos principal name and keytab location must be provided through the `--principal` and `--keytab` arguments to `spark2-submit`.

## Spark integration known issues and limitations

Here are the limitations that you should consider while integrating Kudu and Spark.

- Spark 2.2 (and higher) requires Java 8 at runtime even though Kudu Spark 2.x integration is Java 7 compatible. Spark 2.2 is the default dependency version as of Kudu 1.5.0.
- Kudu tables with a name containing upper case or non-ASCII characters must be assigned an alternate name when registered as a temporary table.
- Kudu tables with a column name containing upper case or non-ASCII characters must not be used with SparkSQL. Columns can be renamed in Kudu to work around this issue.
- `<>` and `OR` predicates are not pushed to Kudu, and instead will be evaluated by the Spark task. Only `LIKE` predicates with a suffix wildcard are pushed to Kudu. This means `LIKE "FOO%"` will be pushed, but `LIKE "FOO%BAR"` won't.
- Kudu does not support all the types supported by Spark SQL. For example, Date and complex types are not supported.
- Kudu tables can only be registered as temporary tables in SparkSQL.
- Kudu tables cannot be queried using HiveContext.

## Spark integration best practices

It is best to avoid multiple Kudu clients per cluster.

A common Kudu-Spark coding error is instantiating extra `KuduClient` objects. In `kudu-spark`, a `KuduClient` is owned by the `KuduContext`. Spark application code should not create another `KuduClient` connecting to the same cluster. Instead, application code should use the `KuduContext` to access a `KuduClient` using `KuduContext#syncClient`.

To diagnose multiple `KuduClient` instances in a Spark job, look for signs in the logs of the master being overloaded by many `GetTableLocations` or `GetTabletLocations` requests coming from different clients, usually around the same time. This symptom is especially likely in Spark Streaming code, where creating a `KuduClient` per task will result in periodic waves of master requests from new clients.