

Securing Streams Messaging Manager 7.2.7

Securing Streams Messaging Manager

Date published: 2020-08-10

Date modified: 2021-01-27

The Cloudera logo is displayed in a bold, orange, sans-serif font. The word "CLOUDERA" is written in all caps, with a stylized 'E' that has a horizontal bar extending to the right.

<https://docs.cloudera.com/>

Legal Notice

© Cloudera Inc. 2025. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents

Securing Streams Messaging Manager..... 4

Verifying the setup..... 6

Securing Streams Messaging Manager

As a cluster administrator, you can combine Kerberos authentication and Ranger authorization to secure the Streams Messaging Manager (SMM) web user interface (UI). After you secure the SMM web UI, the login page appears, which does not appear by default.

About this task

If you deploy SMM without security, the login page is not enabled on the SMM UI by default. When you enable Kerberos authentication, SMM uses SPNEGO to authenticate users and allows them to view or create topics within Kafka by administering Ranger Kafka Policies. For information on enabling browsers to use SPNEGO, see [How to Configure Browsers for Kerberos Authentication](#).

After you secure SMM, anyone within the organization can login to SMM. However, if they do not have the correct policy configuration in Ranger, then they may not have the necessary privileges to perform their required tasks through SMM.

Before you begin

- Configure Kafka in Ranger

For more information, see *Configure a resource-based service: Kafka*.

- Enable Kerberos authentication for Kafka

For more information, see *Enable Kerberos authentication*.

- Add and configure SMM


For more information, see *Creating your first Streams Messaging cluster*.



Note: For the Kafka Client security protocol, it is possible to use INFERRED, SASL_PLAINTEXT, and SASL_SSL for securing SMM. However, Cloudera recommends using SASL_SSL.

Procedure

1. Go to Cloudera Manager > SMM , and click Configuration.
2. Enable Ranger for SMM.



3. Go to the Ranger service UI and configure the Kafka policies.



Note: Review your Ranger Kafka Policies. Remember to log in to Ranger with a user that has the Ranger Admin role.

4. Click cm_kafka in the Ranger service UI.



The List of Policies page appears.

5. Click Add New Policy.

The screenshot shows the Ranger interface for managing policies. The breadcrumb trail is 'Service Manager > cm_kafka Policies'. The page title is 'List of Policies : cm_kafka'. There is a search bar and an 'Add New Policy' button. The table below lists various policies with their IDs, names, labels, status, audit logging, roles, groups, users, and actions.

Policy ID	Policy Name	Policy Labels	Status	Audit Logging	Roles	Groups	Users	Action
22	all - consumergroup	--	Enabled	Enabled	--	--	crusecontrol, streamsmgmr, kafka, streamsmgmr, + More...	[Eye] [Edit] [Delete]
23	all - topic	--	Enabled	Enabled	--	--	crusecontrol, streamsmgmr, kafka, streamsmgmr, + More...	[Eye] [Edit] [Delete]
24	all - transactionalid	--	Enabled	Enabled	--	--	crusecontrol, streamsmgmr, kafka, streamsmgmr, + More...	[Eye] [Edit] [Delete]
25	all - cluster	--	Enabled	Enabled	--	--	crusecontrol, streamsmgmr, kafka, streamsmgmr, + More...	[Eye] [Edit] [Delete]
26	all - delegationtoken	--	Enabled	Enabled	--	--	crusecontrol, streamsmgmr, kafka, streamsmgmr, + More...	[Eye] [Edit] [Delete]
27	ATLAS_HOOK	--	Enabled	Enabled	--	--	hbase, hive, impala, mgov, + More...	[Eye] [Edit] [Delete]
28	ATLAS_ENTITIES	--	Enabled	Enabled	--	--	atlas, rangertagsync, cloudera-scm	[Eye] [Edit] [Delete]
29	ATLAS_SPARK_HOOK	--	Enabled	Enabled	--	public	atlas, cloudera-scm	[Eye] [Edit] [Delete]
30	atlas consumergroup	--	Enabled	Enabled	--	--	atlas	[Eye] [Edit] [Delete]
31	ranger_entities_consumer consumergroup	--	Enabled	Enabled	--	--	rangertagsync	[Eye] [Edit] [Delete]
42	enable-create	--	Enabled	Enabled	--	--	cloudera-scm	[Eye] [Edit] [Delete]

The Policy Details page appears.

The 'Policy Details' page shows the configuration for the 'enable-create' policy. The 'Policy Type' is 'Access'. The 'Policy Name' is 'enable-create' and the status is 'enabled'. The 'Policy Label' is 'Policy Label'. The 'cluster' dropdown is set to 'cluster' and the status is 'include'. The 'Description' field is empty. The 'Audit Logging' is set to 'YES'.

6. Add a policy name and select cluster from the dropdown.

Policy Details :

Policy Type **Access**

Policy Name * **enabled** **normal**

Policy Label **include**

topic
 transactionalid
 cluster
 delegationtoken
 consumergroup

Description

Audit Logging **YES**

7. Type * in the field beside cluster, and select the * from the values that appear.
8. Go to the Allow Condition section and select the user.
9. Add permissions by clicking the + under Add Permissions.

Allow Conditions :

Select Role	Select Group	Select User	Policy Conditions	Permissions	Delegate Admin
<input type="text" value="Select Roles"/>	<input type="text" value="Select Groups"/>	<input type="text" value="x streamsmgmr"/>	Add Conditions +	Add Permissions +	<input type="checkbox"/>
<div style="border: 1px solid #ccc; padding: 5px;"> <p>Exclude from Allow Conditions :</p> </div>					
<input type="text" value="Select Roles"/>	<input type="text" value="Select Groups"/>	<input type="text" value="Select Users"/>	Add Conditions +	<div style="border: 1px solid #ccc; padding: 5px;"> <p>add/edit permissions</p> <p><input type="checkbox"/> Configure</p> <p><input checked="" type="checkbox"/> Describe</p> <p><input type="checkbox"/> Kafka Admin</p> <p><input checked="" type="checkbox"/> Create</p> <p><input type="checkbox"/> Idempotent Write</p> <p><input type="checkbox"/> Describe Configs</p> <p><input type="checkbox"/> Alter Configs</p> <p><input type="checkbox"/> Cluster Action</p> <p><input type="checkbox"/> Alter</p> <p><input type="checkbox"/> Select/Deselect All</p> </div>	<input type="checkbox"/>

10. Select Create and Describe permissions.
11. Click Add.

Related Information

- [Configure a resource-based service: Kafka](#)
- [Enable Kerberos Authentication](#)
- [Creating your first Streams Messaging cluster](#)


Verifying the setup

After you secure SMM, you can verify the security setup. You can login to the SMM web UI and create Kafka topics.

Procedure

1. Go to Cloudera Manager > SMM .


The login page for SMM appears.



The screenshot shows the login interface for Streams Messaging Manager. At the top, there is a dark blue header with the logo on the left and the text "STREAMS MESSAGING MANAGER" on the right. Below the header, there are two input fields: "USERNAME" with the value "tester" and "PASSWORD" with masked characters "*****". A green "SIGN IN" button is positioned below the password field.


2. Login to the SMM UI using your regular credentials.

After you log in, you see the user logout dropdown at the top right corner of your screen. It shows the domain associated with the user.




3. Click Streams Messaging Manager Web UI.

4. To add a topic, go to Topics.



5. Click Add New.








6. Add a topic name, select partitions, and cleanup policy.

Add Topic ✕

TOPIC NAME

PARTITIONS

Availability

				
MAXIMUM	HIGH	MODERATE	LOW	CUSTOM

REPLICATION FACTOR 3	REPLICATION FACTOR 3	REPLICATION FACTOR 2	REPLICATION FACTOR 1	
MIN INSYNC REPLICA 2	MIN INSYNC REPLICA 1	MIN INSYNC REPLICA 1	MIN INSYNC REPLICA 1	

Limits

CLEANUP.POLICY

Advanced

7. Click Save.

You see the following message in the top right corner of the webpage.

